



A9.13-3

00709

# MODERN STEEL CONSTRUCTION



1 *Interstitial Framing Plus* ..... 10  
 2 *A New Beacon on the Hill* ..... 3  
 3 *Prize Bridges of 1973* ..... 12



# MODERN STEEL CONSTRUCTION



Published by

## American Institute of Steel Construction

101 Park Avenue, New York, N. Y. 10017

### OFFICERS

Gilbert M. Dorland, President  
Van W. Coddington, First Vice President  
William R. Jackson,  
Second Vice President  
Robert P. Stupp, Treasurer  
John K. Edmonds,  
Executive Vice President  
Leslie H. Gillette,  
Assistant Executive Vice President  
William W. Lanigan,  
Secretary and General Counsel

### EDITORIAL STAFF

Daniel Farb, Director of Publications  
Mary Anne Donohue, Editor

### REGIONAL OFFICES

Atlanta, Georgia  
Birmingham, Alabama  
Boston, Massachusetts  
Chicago, Illinois  
Cleveland, Ohio  
Columbus, Ohio  
Dallas, Texas  
Denver, Colorado  
Detroit, Michigan  
Charlotte, North Carolina  
Hartford, Connecticut  
Houston, Texas  
Los Angeles, California  
Memphis, Tennessee  
Milwaukee, Wisconsin  
Minneapolis, Minnesota  
New York, New York  
Oklahoma City, Oklahoma  
Omaha, Nebraska  
Philadelphia, Pennsylvania  
Pittsburgh, Pennsylvania  
St. Louis, Missouri  
San Francisco, California  
Seattle, Washington  
Syracuse, New York  
Washington, District of Columbia

VOLUME XIII / NUMBER 3 / THIRD QUARTER 1973

### CONTENTS

A New Beacon on the Hill	3
Inverted Pyramid for Florida Pier	6
A Bridge Within a Bridge	8
Interstitial Framing Plus	10
Prize Bridges of 1973	12

### THE FOURTH ANNUAL T.R. HIGGINS LECTURESHIP AWARD

*The 1974 T. R. Higgins Lectureship Award has been announced nationally to educators, engineers, and architects. Named in honor of the former AISC Director of Engineering and Research, the Award recognizes the author of the technical paper judged to have made the most significant contribution to engineering literature on fabricated structural steel.*

*The Award-winning paper will be selected by a jury of six eminent educators, designers, and industry representatives.*

*They are:*

*Glen V. Berg University of Michigan  
Egor P. Popov University of California, Berkeley  
Stanley D. Lindsey Stanley D. Lindsey & Associates  
Robert D. Vanderlyn Baker-Wibberley & Associates  
Robert D. Paterson Vermont Structural Steel Corp.  
John F. W. Koch International Steel Company*

*The Award winner will be announced on February 5, 1974. Presentation of an engraved certificate and a \$2,000 honorarium will be made at the 1974 AISC National Engineering Conference in Chicago, where an oral review of the prize-winning paper will be presented by the author.*

### THE TWELFTH ANNUAL FELLOWSHIP AWARDS

*The deadline for entries to AISC's 1974 Fellowship Awards Program is February 11, 1974. These awards serve to encourage expertise in the creative use of fabricated structural steel.*

*Four \$2,500 fellowship awards will be granted to senior or graduate students enrolled in a structural engineering program at an accredited engineering institution. Additionally, the head of the department where each Fellow will undertake his study will receive a further grant of \$500 for unrestricted general administrative use.*

*Students interested should contact the Education Committee, AISC, 101 Park Avenue, New York, N.Y. 10017 for the Rules and Instructions for Applicants.*



## A New BEACON on the Hill

**Architect-Engineer:**  
Hoyle, Doran and Berry, Inc.  
Boston, Mass.

**General Contractor:**  
Vappi & Co., Inc.  
Cambridge, Mass.

**Steel Fabricator:**  
Bethlehem Steel Corporation  
Bethlehem, Pa.

Use of steel for the framework of the 22-story John W. McCormack State Office Building, recently erected on Beacon Hill, is resulting in a considerable dollar savings to Massachusetts taxpayers.

The \$25-million structure is being built for the Commonwealth of Massachusetts, Government Center Commission, adjacent to the State House. Partners Austin J. Cribbin, Jr. and Nisso T. Aladjem of Hoyle, Doran and Berry, Inc., Boston architect-engineer for the project, explain:

"The structural steel — in order to gain time — was let as a separate contract about four to five months before the general construction contract was awarded.

"This was possible since we previously designed a newly completed 465-car, 4-level underground garage at the site with provision for steel erection from its roof when the time came. As a result, we could help the state save about five months on the overhead of the general contractor—and realize the use of the high-rise structure perhaps three to four months sooner.

"When you consider that the average rental cost of office space in the Boston area runs about \$9 per sq ft (ranging roughly between \$7.50 to \$12.00 per sq ft of space) any time saved in getting into this 650,000-sq ft office structure can be very valuable to the taxpayers. Now that's a real plus for steel."

The 136-ft by 216-ft by 318-ft-high structure will use 6,100 tons of structural steel shapes and plates.



*The John McCormack State Office Building has realized savings in time and money by selecting structural steel.*

### **Structural Steel**

Columns for the first three stories are made of high strength A588 steel (50,000 psi yield strength). Some of these columns weigh as much as 735 psf. Above the third story, the framework is A36 steel.

Because of an earth fault that exists in the Boston area, the structural framework is designed for Zone Two seismic conditions. Essentially, it is a moment-connected frame rigid in both directions. A490 high-strength bolts have been used for connections in the lower areas, while upper frame areas are connected by A325 bolts.

Typical bays are 30 ft, except for two at 20 ft each. (The 30-ft bays carry through to the garage columns,

which were designed to provide adequate space for vehicles. The column-carrying foundation system in the garage area consists essentially of 6-ft stripped footing mats—similar to spread footings.)

The floor system utilizes a blend of cellular composite steel deck. Basic floor live loads are designed at a relatively high 70 psf (plus 25 psf for partitions) because many of the state offices keep heavy files and records.

Floor-to-ceiling height typically is 8 ft-9 in., while basic roof live load is equivalent to about 80 psf. The roof live load is high because of a 15-ton window washing machine that will move around the roof when required. In fact, it would be possible to land a

helicopter on the roof, if necessary, according to the architect-engineer.

### **Fire Protection**

Applicable building code for the structure is BOCA and the state code. Type 1A fire-resistant construction (four hours for columns, three hours for floors) is used throughout.

Guy A. Carbone, Chief Engineer of the Government Center Commission notes:

"Of prime importance during the design of the building was the safety and comfort of its future occupants. As a result of our concern, we incorporated into the structure a prototype advanced system for smoke evacuation and other safety measures."

Ceiling mounted ionization-type smoke detectors are strategically located on each floor throughout the building, according to Mr. Carbone. These firestats and smoke detectors, when activated, automatically and immediately start a smoke evacuation system, identify and annunciate the location of the detector activated, notify the Capitol Police, and summon the Boston Fire Department. This is all done simultaneously.

Because the building is 22 stories and will house approximately 3,000 occupants when it is operational, the chief engineer said that the entire building will not be evacuated when an alarm is sounded.

Instead, a visual and audio alarm will be set off automatically on the involved floor and the floor directly above the floor involved. At that time, preassigned fire marshals and/or their back-up personnel on the affected floors will initiate a predetermined procedure leading the occupants on those floors to safety.

When the firefighters arrive, designated Fire Department officials will assume command and, in conjunction with the Capitol Police, may selectively evacuate further areas of the building or the entire building by sounding appropriate alarms and giving instructions over a public address system installed throughout the building. A central control station is located in the Capitol Police headquarters. This station will be the nerve center when emergencies arise.

Mr. Carbone adds that "Naturally, we are concerned with panic by occupants should a fire emergency occur. Accordingly, we have made extensive arrangements for two-way communication between the central console, located in the Capitol Police area of the building, and the fire pump room and firefighters at standpipe connections at each floor. Fast and accurate information will be disseminated to the firefighters and the occupants of the building."

The smoke evacuation system is generally comprised of large fans which supply air to the floor involved and the floors directly above and be-

low the involved floor. Exhaust fans remove harmful air and smoke from these three floors. A minimum of 30 air changes per hour will be simultaneously exhausted from all corridors on these three floors. In addition, smoke is evacuated from all stairwells, creating a sheltered route for movement of occupants.

Also, elevators will be controlled from a central control switch and selectively operated. There is no danger of elevators automatically stopping on floors involved in a fire. According to Mr. Carbone, the entire system is "fail safe" and can be run on emergency power.

Sprinklers, while not provided throughout the building, are located in designated areas. Provisions also are made for future connections to the sprinkler standpipes at each floor. Two 1,000-GPM fire pumps serve the building, each connected to an emergency power system.

**Other Features**

The new John W. McCormack building has been completely designed to accommodate the needs of the handi-

capped, many of whom are employed by the Commonwealth. For example, for the blind there will be braille-designated buttons on the elevators and special knurled doorknobs on doors leading to dangerous areas. Ramps and prudently located electrical devices will be installed for occupants in wheelchairs. Special drinking fountains, flashing lights, and buzzers will also assist the handicapped.

"As for the exterior of the structure," notes Mr. Carbone, "we tried to construct the building to blend harmoniously with the very sensitive surrounding area, which includes Beacon Hill and the State House. For this and other reasons, we limited the height of the building to approximate the height of pre-existing surrounding buildings.

"The architect has designed a facade of bronze-tinted glass, highlighted by warm precast concrete column covers comprised of a carefully blended amount of white cement with pink granite and quartz aggregates."

Occupancy is scheduled for early in 1975.

*A588 steel was used for columns in the first three stories. The framework for the upper stories is A36 steel.*



# Inverted Pyramid for Florida Pier



St. Petersburg's "Million Dollar Pier" is coming to life again via a municipal pier complex. Situated at the edge of a pier, and extending into the waters of Tampa Bay, the main building — a new landmark — provides a terminus for the street approach from city to bay, and at the same time maintains an openness at the end of the pier for viewing the water and the cityscape.

## Reversed Pyramid

This unusual building has five levels open to the public. The design keeps the main pier open with the smallest space of 60 ft square at the base of the project; each successive floor expands in a "reversed pyramid" form to produce the greatest floor area, 150 ft square at the top of the building, without obstructing the lower level pier area.

On the first level a glassed-in lobby area is centered with a two-story "rain curtain" fountain related to the second

level by a large circular opening. The second level will be used for exhibitions, art shows, and small receptions.

The multi-purpose third level has 10,000 sq ft of floor space that can be subdivided into several small meeting rooms or opened up for large meetings. A stage, along with portable seating arrangements, could convert the space into an auditorium, or the area can be used as a dance floor.

A restaurant, cocktail lounge and banquet room, with a seating capacity of 600, comprises the fourth level, taking advantage of the excellent view of the city and the sea from the higher elevation.

The fifth level is sun deck, promenade, and glass enclosed observation deck. The roof deck is designed to be covered in a future expansion, retaining a 15-ft promenade for observation on the perimeter. Mechanical equipment takes up the entire sixth level.

## Architect:

Harvard & Jolly, AIA  
St. Petersburg, Fla.

## Structural Engineer:

Erwin Reiss  
St. Petersburg, Fla.

## General Contractor:

Batson-Cook Co.  
Jacksonville, Florida

### Structural Design

Surrounding the main structure are six one-story buildings housing specialty shops. These create interesting landscaped malls, courts, and exterior spaces well scaled to the pedestrian.


Architectural considerations dictated a 15-ft grid module with uniform fixed vertical heights. This required careful coordination with the structural and mechanical designs. A two-way continuous floor system was selected; the deep beams required for the system permitted the more than 200 penetrations required for the high velocity air conditioning ducts, as well as other horizontal piping.

To facilitate erection, stubs of the diagonal strut members were shop welded to the horizontal framing. The remainder of the diagonal strut members were then field welded to the stubs using splice plates. The corner diagonals support as much as 500 tons. The all-welded structural frame was X-ray and ultrasonic tested. All structural steel was A572. The structure is designed for the hurricane and wind loads of the coastal area.



*The corner diagonals support up to a 500 ton load.*

*The "reversed pyramid" shape produces a floor area of 150 ft square at the top of the building.*



# A BRIDGE WITHIN A BRIDGE

by Robert F. Victor and Ciprian A. Pauroso




Restoration of the 132-year-old covered bridge over the Housatonic River between Sharon and Cornwall on Connecticut Route 128 involved unusual and complex construction. A major part of the construction called for an orthotropic steel deck bridge.

The plans for restoring the span grew out of opposition by local residents to original plans of the Connecticut Department of Transportation to build a new multimillion dollar bridge and only retain the existing bridge for historical purposes. The old bridge had a load limit of only four tons. These plans were subsequently dropped and state engineers worked cooperatively with local officials and interested citizens to develop the mutually accepted design which preserved the covered bridge and made it fully serviceable for traffic.

The heart of the construction that makes this a modern load-carrying bridge is the separate orthotropic steel deck bridge enclosed within the old structure. The orthotropic deck is composed of thin, high-strength steel plates welded together to form a complete one-piece bridge deck. The new orthotropic bridge, not attached to the trusses of the old structure, supports itself and vehicular loads independently. The old structure now just supports itself. This "bridge within a bridge," one of the few orthotropic bridges constructed in the United States, is probably the first ever built inside a covered bridge.


To work on the covered bridge, a temporary 200-ft one-way bridge was built on the south side of the present bridge. This allowed the covered bridge to be closed to traffic and restoration to take place. The floor of the old bridge was removed. The old bridge was jacked up off the existing substructure to a new permanent elevation two feet higher to protect it



Interior, underside, and cross-sectional views of the restored covered bridge over the Housatonic River, Conn.

Mr. Victor is Senior Highway Engineer, Connecticut Dept. of Transportation, Bureau of Highways, Bridge Design Section, Wethersfield, Conn.  
Mr. Pauroso is AISC Regional Engineer in Hartford, Conn.





from future flood waters. Also new abutments inside the old were built to support the orthotropic bridge.

The deck plate of the orthotropic bridge is  $\frac{3}{8}$ -in. thick (based on L/300 deflection criteria between rib walls) and 14 ft wide. The bridge has 5 ribs at 2 ft o.c. Brake press formed, the ribs are 9-in. deep,  $\frac{5}{16}$ -in. thick, 6.5-in. and 12.12-in. wide at the bottom and top respectively, and are trapezoidal in shape. The ribs are joined to the deck plate by 80 percent penetration groove welds.

The two main girders are 11 ft apart and each consists of an  $1\frac{1}{4}$ " x 18" bottom flange plate and  $\frac{3}{8}$ " x 22" web, fillet welded to the deck plate. Two edge plates ( $\frac{3}{8}$ " x 6") are welded to each edge of the deck plate by partial penetration groove welds.

The bridge is two-span continuous (93' - 75' spans) with each end cantilevered out from the bearings to form a total deck length of 172.55 ft. In the longer span, floor beams are 15.5 ft o.c.; in the shorter span 15 ft o.c.

A  $\frac{1}{2}$ " x 6" bottom flange and a  $\frac{3}{8}$ " x 22" web (castellated to tightly fit around the ribs) form the floor beams which are fillet welded to the deck plate and ribs. The web is fillet welded directly to the girder webs and the bottom flange is butt welded to the girder bottom flange. Trapezoidal plates ( $\frac{3}{8}$ " x 22" deep) stiffen the deck plate outside the floor beams.

At each end of the bridge, the ribs are seal welded to the last floor beam. Trapezoidal plates ( $\frac{3}{8}$ " x 22") support the end of the deck plate. An edge plate is welded to the end of the deck plate.

All steel is A588. A protective coating system was used on top of the deck plate under the wooden decking. A four-coat system was used: a weldable, pre-construction, inorganic zinc primer, an inorganic zinc prime coat, and two topcoats of a high-build winter grade epoxy polyamide.


The prefabricated steel bridge was brought to the bridge site in three full width (14 ft) sections of 61, 61,

and 50.5 ft. These sections were joined with two full width splices using a combination of welding the deck plate and high-strength bolting the ribs and main girders. After making the splices, the new steel deck bridge was pulled from one bank to the other, as was done with the original covered bridge.

To put the finishing touches on the bridge, a diagonal plank wooden floor was bolted to the steel deck with threaded welded studs. Wood curbing was installed and the interior white-washed to complete the inside work. Outside, the roof was reshingled with white cedar shingles and the siding was painted barn red.

**Designer:**  
Connecticut Dept. of Transportation  
Bureau of Highways  
Bridge Design Section  
Wethersfield, Conn.

**General Contractor:**  
De Fonce Construction Corp.  
Bridgeport, Conn.



# Interstitial Framing Plus

by Dennis Brizee, AIA

Versatility of the interstitial framing concept can be seen in the new addition to a Tucson, Ariz., hospital. After studying existing interstitial designed hospitals, the architects came up with a different approach to the design, at no additional cost.

Generally, the interstitial system consists of a series of primary trusses or load bearing walls, which support a secondary joist system. The mechanical and electrical equipment, along with service catwalks, are usually housed in this space in existing interstitial hospitals, often restricting mobility within the interstitial area.

The new system at St. Joseph's Hospital comprises a corrugated metal deck, covered with insulating lightweight concrete fill, which spans between the bottom chords of the trusses to create a total working/maintenance floor. Top and bottom chords of the

trusses are completely stayed laterally by the steel deck, with only temporary bridging required during erection.

This new approach offers features not found in hospitals first using the interstitial system, yet costs the same as the conventional interstitial design.


Because the interstitial floor with its lightweight insulating concrete/metal deck is a fireproofing membrane, fire sprinklers, normally required in the interstitial space, are not necessary; neither was fireproofing of the trusses. One of the hazards of the catwalk system is the noise level made by workmen in the interstitial space and transmitted to patient areas below. The insulating metal deck in the new system acts as a buffer to keep the noise level to a minimum.

To provide large open spaces for future flexibility requires long spans and minimum use of interior columns, but reduces the framing needed to effectively support lateral loads produced by wind and earthquake forces. Resistance to lateral forces was therefore provided by diaphragm action of

the floor structure spanning between reinforced concrete shear walls located at either end of the building. The public areas, not encompassing the interstitial space floor, have 3-in. deep V-shaped metal decking topped with a 4½-in. concrete surface. This typical floor system acts as a supported horizontal beam (diaphragm), spanning 290 ft between vertical shear walls that cantilever from the foundations. Gravity loads are transmitted from the trusses to the precast concrete columns through corbels cast integrally with the columns. Lateral loads are transmitted from the floor decks to the columns and shear walls by studded wall plates and edge angles with field welded connections.

C-shaped columns carry all conduit and pipe between the various floors of the hospital. These concrete columns are accessible from the exterior by hinged metal door units, while the interior side of the column or the web of the channel unit has openings into the interstitial space at each level by conventional metal doors.

Mr. Brizee is senior vice president in the firm of William Wilde and Associates, Inc., Architects, Tucson, Ariz.




**Architects:**  
 William Wilde and Associates, Inc.  
 Tucson, Ariz. and Los Angeles, Calif.

**Structural Engineer:**  
 Morris Self  
 Gainesville, Fla.

**General Contractor:**  
 M. M. Sundt Construction Co.  
 Tucson, Ariz.

**Steel Fabricator:**  
 Robberson Steel Company  
 Oklahoma City, Okla.

*A corrugated metal deck spans between the bottom chords of the trusses to create a working maintenance floor.*



*Partial perspective of structural system, St. Joseph's Hospital.*

# PRIZE BRIDGES OF 1973



▲ PRIZE BRIDGE 1973 — LONG SPAN

**Atchafalaya River Bridge**  
Simmesport, La.

**Designer:** Modjeski and Masters

**Owner:** Louisiana Dept. of Highways

**General Contractors:**

*Superstructure:* John F. Beasley Construction Company

*Substructure:* Massman Construction Company

**Fabricator:** Vincennes Steel Corporation,  
Division of NOVO Corporation

**Erector:** John F. Beasley Construction Company



▲ PRIZE BRIDGE 1973 — MEDIUM SPAN, LOW CLEARANCE

**Railway Bridge, LL Line Over N. P. Ry. & LD 5 Line**  
Woodland, Wash.

**Designer:** Washington State Highway Commission

**Architectural Consultant:** Edward J. Green, AIA

**Owner:** State of Washington

**General Contractor:** Peter Kiewit Sons' Co.

**Fabricator:** Isaacson Structural Steel Company,  
Division of Isaacson Corporation

**Erector:** Peter Kiewit Sons' Co.



▲ PRIZE BRIDGE 1973 — SHORT SPAN

**Hatfield Bridge**  
Hatfield, Wisc.


**Designer:** Owen Ayers & Associates

**Owner:** Jackson County Highway Dept.

**General Contractor:** Lunda Construction Company

**Fabricator:** Phoenix Steel Corporation

**Erector:** Lunda Construction Company



▲ PRIZE BRIDGE 1973 — HIGHWAY GRADE SEPARATION

**Glen Lily Road No. 2 Over Green River Parkway**  
Bowling Green, Ky.

**Designer:** Kroboth Engineers, Inc.

**Owner:** Commonwealth of Kentucky, Dept. of Transportation

**General Contractor:** Peter Kiewit Sons' Co.

**Fabricator:** Peden Steel Company

**Erector:** Nashville Bridge Company

**PRIZE BRIDGE 1973 — ELEVATED HIGHWAYS OR VIADUCTS**

**Latah Creek Bridge**

Spokane, Wash.

Designer: Howard Needles Tammen & Bergendoff

Owner: Burlington Northern

General Contractor: Hensel Phelps Construction Company

Fabricator: Kansas City Structural Steel Co.

Erector: Don L. Cooney, Inc.



**PRIZE BRIDGE 1973 — MOVABLE SPAN**

**Harvey Canal Bridge**

Jefferson Parish, La.

Designer: de Lauro Engineers, Inc.

Owner: Jefferson Parish, Dept. of Roads & Bridges

General Contractor: Boh Bros. Construction Co., Inc.

Fabricator/Erector: Bristol Steel & Iron Works, Inc.



**PRIZE BRIDGE 1973 — SPECIAL PURPOSE**

**Pedestrian Overpass At Avenue Z**

San Angelo, Tex.

Designer/Owner: Texas Highway Dept.

General Contractor: HCW Construction Co., Inc.

Fabricator: Robberson Steel Company

Erector: HCW Construction Co., Inc.



**AWARD OF MERIT 1973 — LONG SPAN**

**Piscataqua River Bridge**

Portsmouth, N. H. - Kittery, Me.

Designer: Hardesty & Hanover

Owners: State of Maine, Dept. of Transportation

State of New Hampshire, Dept. of Public Works & Highways

General Contractors: Bethlehem Steel Corporation


Cianbro Corporation

Fabricators: Bancroft & Martin Inc.

Bethlehem Steel Corporation

Erectors: Bethlehem Steel Corporation

Cianbro Corporation



**AWARD OF MERIT 1973 — LONG SPAN**

**I-80 over Missouri River**

Omaha, Neb. - Council Bluffs, Ia.

**Designer:** Howard Needles Tammen & Bergendoff

**Owners:** Iowa State Highway Commission  
Nebraska Dept. of Roads

**General Contractors:**

*Superstructure:* Pittsburgh-Des Moines Steel Company

*Substructure:* Jensen Construction Company

**Fabricator:** Pittsburgh-Des Moines Steel Company

**Erector:** John F. Beasley Construction Company

**AWARD OF MERIT 1973 — MEDIUM SPAN, HIGH CLEARANCE**

**Adlerpoint Bridge**

Eel River at Alderpoint, Calif.

**Designer/Owner:** County of Humboldt, Dept. of Public Works

**General Contractor:** Lew Jones Construction Co.

**Fabricator/Erector:** Kaiser Steel Corporation



**AWARD OF MERIT 1973 — MEDIUM SPAN, HIGH CLEARANCE**

**Green River Bridge**

Henderson County, N. C.

**Designer/Owner:** North Carolina Dept. of Transportation  
and Highway Safety

**General Contractor:** Wannamaker and Wells, Inc.

**Fabricator/Erector:** American Bridge Division, United States Steel

**AWARD OF MERIT 1973 — MEDIUM SPAN, HIGH CLEARANCE**

**Missouri Highway 7**

Over South Arm of Harry S. Truman Reservoir

Warsaw, Missouri

**Designer:** Harrington and Cortelyou, Consulting Engineers

**Responsible Agency:** U.S. Army Corps of Engineers,


Missouri River Division

**Owner:** Missouri State Highway Commission

**General Contractor:** Anderson Construction Company

**Fabricator:** Kansas City Structural Steel Co.

**Erector:** Anderson Construction Company



00707



**AWARD OF MERIT 1973 — MEDIUM SPAN, LOW CLEARANCE**

**Eagle River Bridges On I-70**

West of Wolcott, Colo.

**Designer/Owner:** State of Colorado, Division of Highways

**General Contractor:** A. S. Horner Construction Co., Inc.

**Fabricator:** The Midwest Steel & Iron Works Co.

**Erector:** A. S. Horner Construction Co., Inc.

**AWARD OF MERIT 1973 — HIGHWAY GRADE SEPARATION**

**East Evergreen Interchange**

West of Denver, Colo.

**Designer/Owner:** State of Colorado, Division of Highways

**General Contractor:** Northwestern Engineering Company

**Fabricator:** The Midwest Steel & Iron Works Co.

**Erector:** Northwestern Engineering Company



**AWARD OF MERIT 1973 — HIGHWAY GRADE SEPARATION**

**Ridge Road Arch Over I-70**

West of Frederick, Maryland

**Designer:** Green Associates, Inc.

**Owner:** Maryland Dept. of Transportation

**General Contractor:** C. William Hetzer, Inc.

**Fabricator/Erector:** Pittsburgh-Des Moines Steel Company



**AWARD OF MERIT 1973 — ELEVATED HIGHWAYS OR VIADUCTS**

**West Connector Viaduct**

San Jose, Calif.

**Designer:** California Division of Highways, Bridge Dept.

**Owner:** State of California


**General Contractor:** Lew Jones Construction Co.

**Fabricator/Erector:** Pittsburgh-Des Moines Steel Company

AMERICAN INSTITUTE OF STEEL CONSTRUCTION  
101 Park Avenue • New York, New York 10017

Address Correction Requested

BULK RATE  
U.S. POSTAGE  
PAID  
NEW YORK, N.Y.  
Permit No. 6662



AWARD OF MERIT 1973 — SPECIAL PURPOSE  
Pedestrian Bridge Over Wantagh State  
Parkway at Beltagh Avenue  
Wantagh, New York

Designer: Andrews & Clark, Inc.  
Owner: Long Island State Park and Recreation Commission  
General Contractor: Horn Construction Co., Inc.  
Fabricator: R & M Steel Corp.  
Erector: Horn Construction Co., Inc.

AWARD OF MERIT 1973 — SPECIAL PURPOSE  
Elevated PRT Guideway Over Monongahela Blvd.  
Morgantown, W. Va.

Designer: Frederic R. Harris, Inc.  
Sponsor: Urban Mass Transportation Administration  
General Contractors: Trumbull Construction Company  
Fabricator: The Allied Metals Company  
Erector: Connell Steel Erectors

