

MODERN STEEL CONSTRUCTION



January 1995

\$3.00




Renovation



- Common names include: interlocking, button punch, and bayonet side lap.
- Can be button punched, welded, or screwed.
- Horizontal return on "female" lip.



- Common names include: interlocking and button punch and bayonet side lap.
- Can only be button punched.
- No horizontal return on "female" lip.



Stitch Connector

A "Stitch" Connector is a side lap connector that attaches adjacent sheets at their sides.


Side Lap Types




- Common names include: overlapping, barge and foot, and nestable.
- Can be welded or screwed.




- Provides adjustment when required.



* Note: In general the nomenclature is "cover width"/(number of welds).




deck connection terms



Welding Washer

- Welding washers are to be used on deck products lighter than 22 gage (0.028"). Do not use welding washers on side laps.

Typical Frame Fastener Layouts for roof deck



NICHOLAS J. BOURAS, INC.
P.O. BOX 662, 475 SPRINGFIELD AVE.
SUMMIT, NEW JERSEY 07902 - 0662
(908) 277 - 1617




0948

ARBED *Tailor-Made* *Beams speed repairs of* *nation's oldest steel bridge.*

Gateway Western Railway's bridge at
Glasgow, MO. after the flood of July 1993.

60 days after award; thanks to 140 tons of
ARBED W44 x 335 Tailor-Made Beams.



Constr. Mgr.: Design Nine, Inc. St. Louis, MO.
Photography : Dale Graham, Fayette, MO.

Fabricator : Phoenix Steel, Inc., Eau Claire, WI.
Erector : St. Louis Bridge Co., Arnold, MO.

Consulting Engineers: Modjeski & Masters, New Orleans, LA.

Steel supplier: 140 tons of ARBED W44x16x335 rolled WTM (Tailor-Made) beams in ASTM A572/Gr50,
from the TradeARBED stock in Blytheville, AR.

When you need Big Beams, Service and Quality; The name is **ARBED**.

WTM (Tailor-Made) rolled beams are available in 24" through 44" and from 129 lbs/ft through 798 lbs/ft; in ASTM A36, A572, A709 with most sections available in ARBED's new **HISTAR®** Grade 65 (ASTM A913). Sectional properties are available on a free floppy disc (Lotus 1-2-3, Quattro Pro and ASCII versions for IBM, Excel for Macintosh) and the complete **ARBED** database is ready to use in the design softwares GTSTRUDL, ETABS, SAP90 and STAAD-III.

HISTAR® is a registered trade-mark of ARBED

For complete information, availability, literature and floppy disc,
contact one of our TradeARBED offices at the following locations:


- 825 Third Ave., New York, NY 10022. (212) 486-9890, Fax (212) 355-2159.
- 60 E. Sir Francis Drake Blvd., Suite 202, Larkspur, CA 94939 (415) 925-0100, Fax (415) 461-1624 / 8257.
- 390 Brant Street, Suite 300, Burlington, Ontario, Canada L7R 4J4. (905) 634-1400, Fax (905) 634-3536.

Please circle # 35

MODERN STEEL CONSTRUCTION

Volume 35, Number 1

January 1995



Not only did a former steam plant need to be reconfigured to accommodate the needs of a pharmaceutical research company, but it also had to be brought up to current seismic code. The story behind this project begins on page 36.

FEATURES

- 15 STRUCTURAL STEEL SHAPE AVAILABILITY**
A listing of available shapes from the major producers of structural steel members and tubing
- 24 RENOVATION REMEDIES STRUCTURAL HEADACHES**
Renovating a vintage 1917 concrete building with planar steel frames allowed Boston University to modernize a laboratory while adding additional space
- 30 EXTERNAL BRACING PROVIDES SEISMIC SUPPORT**
The retrofit of a 1960s university building was economically accomplished with a system of external steel braces
- 36 INDUSTRIAL REVOLUTION**
An outdated, yet historic, steam plant proved the perfect new home for a pharmaceutical research company
- 45 STRUCTURAL ENGINEERING SOFTWARE SURVEY**
More than 400 structural engineers rated 21 computer programs

DEPARTMENTS

- 6 EDITORIAL**
- 9 STEEL INTERCHANGE**
- Criteria for using mechanically attached grating for lateral bracing
 - Deflection limits for cranes
 - Prevention of back-off of nuts
- 12 STEEL NEWS**
- John D. Griffiths
 - Seminar Series Video Tapes
 - Correspondence
 - National Steel Construction Conference
- 45 STRUCTURAL ENGINEERING SOFTWARE**
- 54 STEEL MARKETPLACE**
- 54 AD INDEX**

Modern Steel Construction (Volume 35, Number 1). ISSN 0026-8445. Published monthly by the American Institute of Steel Construction, Inc., (AISC), One East Wacker Dr., Suite 3100, Chicago, IL 60601-2001.

Advertising office: Facinelli Media Sales, 2400 E. Devon Ave., Suite 257, Des Plaines, IL 60618 (708) 699-6049.


Subscription price:
Within the U.S.—single issues \$3;
3 years \$85.
Outside the U.S.—single issues \$5;
1 year \$36; 3 years \$100.

Postmaster: Please send address changes to Modern Steel Construction, One East Wacker Dr., Suite 3100, Chicago, IL 60601-2001.

Second class postage paid at Chicago, IL and at additional mailing offices.

It's tomorrow ...

in Computerized Structural Engineering



Experience STAAD - III

"Concurrent Engineering" on DOS/Windows/Unix/NT

Welcome to tomorrow in Computerized Structural Engineering. The latest release of STAAD-III, based on the principles of "Concurrent Engineering", is redefining the way you engineer your structure. Whether you are on DOS, WINDOW, UNIX, or NT, STAAD-III is guaranteed to enhance the performance and productivity to a whole new level.

STAAD-III, from Research Engineers, is an acknowledged world leader in structural software. State-of-the-art Static/Dynamic/ Nonlinear analysis, innovative finite element techniques, comprehensive Steel/Concrete/Timber design, powerful graphics and seamless CAD integration have always been our forte. Our deep rooted R & D base, spread over four continents, and our association with the world's leading institutions, have resulted in a solid technological foundation for STAAD-III.

Today's STAAD-III, brings you the latest in modern Computer Aided Engineering. Based on the principles of "concurrent engineering", it unifies leading-edge graphics and visualization techniques with proven and time tested analysis/design. A live and unified associative data base provides seamless integration across all mission critical applications, from concept design and analysis to detail design, simulation and visualizations. Today's STAAD-III - a productivity concept for tomorrow.

With over 10,000 installations, more than 30,000 engineers worldwide rely on STAAD-III for the state-of-the-art in technology.

Experience tomorrow today - experience STAAD-III



Research Engineers, Inc.

22700 Savi Ranch Pkwy., Yorba Linda, CA 92687

Tel: (714) 974-2500 Fax: (714) 974-4771 Toll Free: (800) FOR-RESE

• USA • UK • GERMANY • FRANCE • CANADA • JAPAN • KOREA • NORWAY • TAIWAN • INDIA

Please circle # 34

Qualified Optimism

FOR THE PAST FEW YEARS, JANUARY HAS BEEN A PRETTY DEPRESSING TIME OF THE YEAR FOR ME. I guess it's been a combination of post-Christmas blahs, the awful Chicago winters and a depressed construction market. But 1995 is shaping up to be quite different, and not just because I'm looking forward to my upcoming nuptials. In addition to my personal pleasure, this is the first time since the end of the boom years of the late 1980s that I've heard anyone express optimism about the non-residential construction market.

The buzz started, at least for me, a few months ago at a Peddinghaus open house. Big pieces of fabrication equipment (these things cost in the hundreds of thousands of dollars) were selling—well, maybe not like hot cakes, but at a rate no one had seen for at least several years. A couple of large fabricators were in the office not too long afterward, and they actually had some smiles on their faces. And to top it all off, not once, not twice, but three times in the past month I've spoken with engineers about writing articles on interesting projects and have been told that they were too busy with new work to talk about their old stuff.

Okay, I know we're not taking about a return to 1989 levels. But I firmly believe we're over the hump. Not only is the amount of work available increasing, but the number of firms out there competing for it has decreased.

However, the market is still going to remain incredibly competitive and I don't think we're finished with the current industry-wide shakeout. There are still some weak firms that are likely to close their doors in the coming months.

The question, then, is what can firms do to make sure they're on solid footing? Whether you're a fabricator or an engineer, the answer is the same: stay current. For fabricators, this means making sure your plant's equipment and software is state-of-the-art. While it may look like an expensive investment now, it will pay off in the long run. For engineers, it means investing the time to stay current with up-to-date design practice (such as LRFD, eccentrically braced connections, partially restrained composite design, and cutting edge design & analysis software).

It also means investing the time and money in continuing education. AISC offers seminars, breakfast meetings and an annual conference (this May in San Antonio). Likewise, ASCE, local fabrication groups, and local engineering associations offer continuing education opportunities. And lastly, consider subscribing to one or more journals—and reading them. Perhaps the best—and most practical—of the bunch is AISC's quarterly *Engineering Journal*. Coming up in the first quarter of 1995, for example, are articles on: *Practical Approaches to Mill Building Columns Subjected to Heavy Crane Loads*; *A Practical Approach to the Leaning Column*; and *Geometrical and Mechanical Properties of Large Rolled Steel Angles*. A one-year subscription costs only \$18 (\$24 outside the U.S.) or \$45 for three years. To receive a subscription, send a check to AISC, P.O. Box 806276, Chicago, IL 60680. **SM**

Editorial Staff

Scott Melnick,
Editor and Publisher
Patrick M. Newman, P.E.
Senior Technical Advisor
Charlie Carter,
Senior Technical Advisor
Jacques Cattan,
Technical Advisor

Editorial Offices

Modern Steel Construction
One East Wacker Dr.,
Suite 3100
Chicago, IL 60601-2001
(312) 670-5407
Fax 312/670-5403

Advertising Sales

Facinelli Media Sales
2400 E. Devon Ave.,
Suite 267
Des Plaines, IL 60018
(708) 699-6049
Fax 708/699-8681

AISC Officers


Frank B. Wylie, III,
Chairman
Robert E. Owen,
First Vice Chairman
H. Louis Gurthet,
Second Vice Chairman
Robert D. Freeland,
Treasurer
Neil W. Zundel,
President
David Ratterman,
Secretary &
General Counsel
Morris Caminer,
Vice President,
Finance/Administration

05600

How to get from here



Estimating Module



Engineering, Analysis and Design Module



Detailing Module



Production Control Module



CNC Interface Module

to here.



Design Data's SDS/2 Steel Fabrication System.

SDS/2 gives you the flexibility to integrate all aspects of your business with one software system. That concept is called Information Management. Each module by itself will save you time and money and by combining products to implement Information Management you receive more than twice the benefit in savings and productivity. So whether you need one SDS/2 software module or all these tools working together, Design Data can provide the most productive system for you.

For more information about SDS/2, information management in the steel industry or future product demonstrations call **800-443-0782**.



"First in...software, solutions, service"
402-476-8278 or 1-800-443-0782

Please circle # 32

© 1992 Design Data Corporation

New Plans and Software for Short-Span Steel Bridges



This two-volume Short-Span Steel Bridge Package contains more than 1,100 predesigned steel superstructures with details, plus user friendly, PC compatible software, that will bring you quick, efficient solutions to many simple-span non-skewed bridges.

The plans tabulate the design of bridges that are 20 feet to 120 feet long in five foot increments for 24, 28, 34, 40 and 44 foot roadway widths. The software provides back-up calculations to the pre-designs and allows the engineer to custom design, code check or rate the bridge.

The package was developed by Dr. S. Taavoni, PE, of Kennedy Porter & Associates for the American Iron and Steel Institute in collaboration with AISC Marketing, Inc. Sponsors of the package include Bethlehem Steel Corporation, Inland Steel Industries, Lukens Steel Co., and U. S. Steel.

With AISI's new comprehensive short-span steel bridge package designers can minimize design time and project cost. Quickly explore design and detail options for:

- Welded plate girders with unstiffened and partially stiffened webs
- Rolled beams with and without cover plates for composite and non-composite construction
- Normal and lightweight concrete deck
- Elastomeric bearings
- Jointless and conventional abutment information
- Crash tested Jersey barrier
- Tables of reactions, moments and deflections
- Table of quantities for each design (structural steel, rebar and concrete)
- AASHTO's Load Factor Design
- HS25 Live Load
- Over 150 11" x 17" design and detail sheets
- Much more!!!

Please send me:

- Information about the AISI Short-Span Steel Bridge Package.
 A copy of the AISI Short-Span Steel Bridge Package (payment enclosed).

Ship Short-Span Bridge Package to:

Name _____
 Company _____
 Address _____
 City _____ State _____ ZIP _____
 Phone _____ Fax _____

FAX: 202-463-6573 or
MAIL: American Iron and Steel Institute
 1101 17th St., NW
 Washington, D. C. 20036
TEL: 202-452-7140



Order Form

Short-Span Bridge Package ___ @ \$150 = \$ ___

Additional shipping and handling will be added for orders outside the U. S.

- Check Visa Mastercard
 (payable to AISI)

Cardholder Name _____

Card Number _____

Expiration Date _____

Signature _____

STEEL INTERCHANGE

Steel Interchange is an open forum for *Modern Steel Construction* readers to exchange useful and practical professional ideas and information on all phases of steel building and bridge construction. Opinions and suggestions are welcome on any subject covered in this magazine. If you have a question or problem that your fellow readers might help you to solve, please forward it to *Modern Steel Construction*. At the same time, feel free to respond to any of the questions that you have read here. Please send them to:

**Steel Interchange
Modern Steel Construction
One East Wacker Dr., Suite 3100
Chicago, IL 60601-2001**

The following responses from previous Steel Interchange columns have been received:

In what instances, if any, and under what criteria can the attachment of grating with mechanical fasteners be used to provide lateral bracing to the compression flange of the members supporting the grating in applications such as walkways and catwalks?

Our company manufactures industrial grade fiberglass grating for walkways and catwalks supported by all medias, i.e. steel, aluminum, stainless steel, timber, and fiberglass beams. Weight reduction is very critical for this type of application, and eliminating cross beams is quite common.

Although design criteria for this type of application is limited, two parameters used for design are:

1. The type of mechanical fasteners used - must be capable to resist cross movement and/or twisting of the compression flange. When tightened, the clamping action should produce the proper friction between grating and beam.

2. Use L_c = maximum unbraced length of the compression flange or 2'-0" maximum to determine fastener spacing.

These two general rules seem to satisfy both the fastening requirements for the grating and lateral support for the compression flange.

Richard L. Cole, P.E.

**Aligned Fiber Composites
Chatfield, MN**

Serviceability is a particular concern for crane systems in industrial buildings but is not clearly covered in the standard code literature. What are deflection limits for crane runway systems?

The references given in a previous Steel Interchange column are mainly concerned with cranes and hoisting equipment. If someone is interested in industry standard references for allowable crane runway deflections, the follow-

Answers and/or questions should be typewritten and double-spaced. Submittals that have been prepared by word-processing are appreciated on computer diskette (either as a Wordperfect file or in ASCII format).

The opinions expressed in *Steel Interchange* do not necessarily represent an official position of the American Institute of Steel Construction, Inc. and have not been reviewed. It is recognized that the design of structures is within the scope and expertise of a competent licensed structural engineer, architect or other licensed professional for the application of principals to a particular structure.

Information on ordering AISC publications mentioned in this article can be obtained by calling AISC at 312/670-2400 ext. 433.

ing are more appropriate:

•Fisher and Buettner, *Industrial Buildings - Roofs to Column Anchorage*, Design Guide 7, AISC, 1993.

•*Guide for the Design and Construction of Mill Buildings*, Technical Report No. 13, Association of Iron and Steel Engineers, Pittsburgh, PA, 1979.

•Merritt, F. S., *Structural Steel Designers Handbook*, McGraw-Hill Book Co., New York, 1972.

•Gaylord, E. H. Jr. and C. N. Gaylord, *Structural Engineering Handbook*, 2nd Edition, McGraw-Hill Book Co., New York, 1972.

Gary J. Davis, P.E.

**Phoenix Engineering Services
South Milwaukee, WI**

Specifications currently exist which require minimum pretensioning loads for slip critical connections. There is, however, no guidance regarding minimum pre-loading of anchor bolts which occur at column bases. While in most situations this issue is academic since the anchor bolt nut and thread projection are below the plane of the concrete slab on grade and are eventually embedded in concrete at the slab isolation joint, there are instances where the nut and thread projection remain exposed. Is tightening the nut to "snug tight" and tack welding the nut to the bolt thread the only solution in preventing the nut from backing off?

Snug tightening and tack welding the nuts is not the only solution to prevent the nuts from backing off. We have specified A449 high strength anchor bolts (tensile strength = 105 to 120 ksi) instead of the ordinary A36 anchor bolts when the structure is subject to fatigue loading.



We pretension the bolt to develop 70 percent of the specified minimum tensile strength of the bolt. The bolt is greased with bondbreaker all the way to

STEEL INTERCHANGE

its end to permit stretching of the bolt while tensioning. The tension is developed into the footing by an adequately designed heavy plate at the bottom of the bolt. To further prevent the nut from loosening (which is not likely to occur for a properly pretensioned bolt), a lock nut or Pal nut can be added to secure the nut after pretensioning.

We used the A449 anchor bolts for a 160' tall steel tubular tower that supports a 600 kW wind turbine unit. The tower was designed to meet the UBC and Eurocode 3 Fatigue Provisions. Eurocode 3, Chapter 9, Fatigue, specifies an extremely low stress range for an ordinary anchor bolt without preloading (the lowest stress range category in the Eurocode). The use of high strength anchor bolts with preloading is apparently the common practice in Europe when the fatigue strength is critical in the structural design.

David L. Koo, C.E.
Warren A Minner & Associates
Bakersfield, CA



New Questions

Listed below are questions that we would like the readers to answer or discuss.

If you have an answer or suggestion please send it to the Steel Interchange Editor, Modern Steel Construction, One East Wacker Dr., Suite 3100, Chicago, IL 60601-2001.


Questions and responses will be printed in future editions of Steel Interchange. Also, if you have a question or problem that readers might help solve, send these to the Steel Interchange Editor.

In the partial plan shown (top & middle), each of the tube beams is to be moment connected to the tube column by welding. All steel is exposed to view of pedestrian traffic, but is protected from the elements. What is an economical procedure for making the joints?

William Dyker
Naperville, IL

How is the L5 x 3 1/2 x 1/2 angle shown in the figure (bottom right) designed? The angle is used as a rail guide for a roll-up door and is bolted to other steel members 12" on center.

Glenn Whritenour
Bechtel Savannah River, Inc.
Augusta, GA



1995 National Steel Construction Conference San Antonio May 17-19



Don't miss the paramount conference for the structural steel design & construction community!



Mark Holland,
chief engineer,
Paxton & Vierling Steel: If you can only attend one

conference this year, make it AISC's National Steel Construction Conference. If you have anything to do with the design, construction or fabrication of steel structures, this conference will provide practical information that will enhance your professional capabilities. Typical of the material presented at the NSCC was my paper last year on Lean Engineering, which presented information on how to accomplish more with fewer resources—a reality faced by many firms today. I also gained valuable insight from many of the other speakers, such as Geoffrey Kulak on bolting, Omer Blodgett on welding, and Larry Griffis on composite design and wind load serviceability issues. And this year I'm looking forward to hearing Eric Kline talking about avoiding field painting problems, Jim Notch speaking on reducing structural steel costs, and Don Sherman on new developments in the use of structural tubes.

The ideal show for:

- Structural Engineers
- Fabricators
- Construction Managers
- Steel Erectors
- Architects

Yes, I want more information on the National Steel Construction Conference. Please immediately send me your 12-page information and registration kit.

Mail this card to AISC or fax at 312/670-5403.

name: _____

company: _____

street address: _____

city/state/zip: _____

telephone: _____

fax: _____

1995 National Steel Construction Conference

San Antonio May 17-19

Seminars For The Fabricated Structural Steel Design & Construction Community:

- Reducing structural steel costs
- Interpreting the Mexican market
- New concepts in industrial building design
- Weldability, fracture mechanics, and metallurgy
- Seismic design solutions after the Northridge Earthquake
- Connections for hollow structural sections
- Protecting your firm from lawsuits
- Effective project specifications
- Inspection of welded and bolted joints
- Economical painting
- Avoiding painting system failures
- OSHA training for fabricators
- EPA legislation
- Improving plant performance
- Fabricating steel tubes
- Fabrication equipment & methods
- Flame straightening technology
- Team building & partnering
- Constructability issues
- Bar coding for material management
- Total quality management

Place
Stamp
Here

American Institute of Steel Construction
One East Wacker Dr., Suite 3100
Chicago, IL 60601-2001

Mark your calendar now!

Registration \$270 for
AISC members (\$320 for
non-members) for three-
day conference and trade
show.

Contact AISC at:
312/670-2400

Our business is based on the same philosophy.

Let's face it. In today's need-it-now world, you don't have to time to deal with companies that make you wait. When you need something, you need it immediately. You simply can't afford to waste any time. Now you no longer

have to wait for steel.

In most cases Chaparral already has it in stock.


That's because Chaparral is a different kind of mill, a stocking mill. Our \$50-million on-site inventory means we can fill over 80% of your orders from stock. That allows us to process special orders and fast track jobs within 72 hours.

Chaparral has made rolling schedules obsolete. So give us a call. Chances are we've got exactly what you need in whatever quantities you need. And we can have it on its way in an instant. What are you waiting for?

300 Ward Road
Midlothian, Texas 76065-9651
Call free (800) 527-7979 U.S. and Canada
Local (214) 775-8241
FAX (214) 775-6120



**CHAPARRAL
STEEL**



IN MEMORY

By Mark V. Holland,
Chief Engineer, Paxton &
Vierling Steel Co.

In October, John D. Griffiths, P.E., former AISC regional engineer and most recently a vice president of engineering at AISC-member Paxton & Vierling Steel Co., passed away.

His contribution to the industry cannot be measured in the papers he wrote or the times he spoke. Nor on his recent contributions, such as helping to develop the modern format of the latest AISC Specifications and Manuals. John's greatest contribution was his passion for his life's work during his more than five-decade career.

He came from an age when an engineer would sign in at a hotel and put behind their name "P.E.". It always saddened him to see engineers use disclaimers and approver notes in an attempt to dilute their responsibility. John would always get annoyed by engineers who tried to over-complicate the behavior of steel. One of his favorite questions for them was to ask them, through examples, to explain how adding stiffness to a frame could cause it to collapse.

I was one of the lucky young engineers who was able to work under John's tutelage. I remember once computing the shear center of an odd shape. After several hours and many pages of triple integrals, I proudly showed John my work. With only a few lines of simple calculations, he approximated my answer closer than any shop tolerance would require. What the steel industry will be missing, with the passing of John and of men like him, is this practical, accurate and simple understanding of the behavior of steel.

"INNOVATIVE PRACTICES IN STRUCTURAL STEEL" VIDEO NOW AVAILABLE

Though issued too late for Christmas, structural engineers, fabricators and others involved with the design, fabrication or construction of steel-framed buildings can give themselves a late present by purchasing a video-tape version of AISC's popular "Innovative Practices In Structural Steel."

The four-tape series includes information on the latest advances in structural engineering software; an overview of the changes in the 1993 Load and Resistance Factor Design (LRFD) Specification; NEHRP seismic provisions; semi-rigid composite connections, and a look at recent changes in the steel industry and how they affect designers and contractors.

An overview of future technological developments, such as the automated erection system being developed at ATLSS Laboratories, also is presented.

Filmed during the Chicago seminar last year, featured speakers are: Raymond H.R. Tide, former AISC regional engineer and currently a senior consultant with Wiss Janney Elstner in Northbrook, IL; Steve Schneider, Ph.D., an assistant professor at the University of Illinois; Gus Bergsma with Ram Analysis; Robert Lorenz, AISC director of education and training; and Andy Johnson, vice president of AISC Marketing, Inc.

Cost of the video package is only \$75 plus \$5 for shipping & handling (additional sets of handouts are available for \$15 each). In addition to the four videotapes, the package includes the full set of handouts from the lecture. Included are: a copy of the LRFD Specification; an introductory booklet presenting an overview of the Specification; "Interim Guidelines for Repair of Steel Moment Frames & Design of New Connections in High Seismic Zones"; NEHRP recom-

mended seismic provisions; and a two-booklet set of lecture notes featuring copies of slides presented during the seminar.

To order, send a check to: AISC Marketing, Inc., P.O. Box 806286, Chicago, IL 60680-4124 or fax an order (please include your Visa or Mastercard account number along with an expiration date) to: 312/670-5403.

CORRESPONDENCE

(From time-to-time, AISC receives questions of a non-technical nature. When these questions are of general interest, they are printed in *Modern Steel Construction*.)

Q: *May an AISC Certified Category II or III plant certify another steel fabricator to be AISC Certified to fabricate structural steel members?*

A: No. If a contract requires AISC certification of a fabrication shop, the subcontractor's shop also must be certified by AISC. This certification can only be issued by AISC after submission of the proper application material and a satisfactory review.

However, if the contract does not specifically call for AISC certification, then certified fabricators can qualify all of their subcontractors and suppliers, including detailers, steel suppliers and subcontract fabricators. How this qualification is done is up to the fabricator, except that any qualifications required by the contract must be extended to the subcontractor.

—Tom Schlafly,
AISC Director of
Fabricating Operations
& Standards

NATIONAL STEEL CONSTRUCTION CONFERENCE EXPANDS SCOPE

IN ADDITION TO ITS TRADITIONAL AUDIENCE OF STRUCTURAL ENGINEERS AND FABRICATORS, AISC's National Steel Construction Conference is opening its doors to construction managers in 1995. The conference, scheduled for May 17-19 in San Antonio, TX, will feature four professional tracks: Construction Management; Steel Fabrication; Structural Engineering; and Engineering Management. In addition, the conference will include a product exhibition with nearly 100 booths.

"We wanted to expand the conference to involve more of the construction industry," explained Franklin B. Davis, chairman of the AISC NSCC Committee and president of Precise Fabricating. "It's an exciting change that will put more life and spirit into the program."

While seminars are assigned to a specific track, show organizers stressed that there is no additional charge for crossing from one track to another. Registration for the show costs \$320 (\$270 for AISC members) and includes admission to all seminars and general sessions, as well as the trade show. To receive a registration packet, write AISC, One East Wacker Dr., Suite 3100, Chicago, IL 60601-2001 or call 312/670-2400.

Speakers this year include:

- Duane Miller (Lincoln Electric Co.) on welding inspections;
- Jim Scotti (Brown and Root) and Peter Van Nort (H.B. Zachry) on team building/partnering;
- David Harwell (Central Texas Iron Works) on bar coding;
- J.J. Suarez (Belcan) on quality management;
- Eric S. Kline (KTA-Tator) and David Boyd (The Vulcan Group) on paintings and coatings;
- Ken Lee (Goldberg and

Simpson) on recent EPA legislation;

- Buck Rogers (Controlled Automation) on preventive maintenance;
- Jim Blackburn (Vernon Tool Co.) on hollow structural section fabrication;
- Tom Webb (Fibre-Metal Products Co.), Joe Derkitch (National Research) and James Morton on new developments in fabrication equipment and methods.
- R. Richard Avent (Louisiana State University) on flame straightening technology;
- Holley Fisk, Phil Fortune and Tag Wilson on how to protect your firm from lawsuits;
- Donald Buettner (Computerized Structural Design) on steel erection awareness;
- Bob Shaw (Steel Structures Technology Center), A.J. Julicher, and John T. Holcomb (Berlin Steel Co.) on the inspection of welded and bolted joints;
- Jim Notch (Notch & Associates); John Nagel (AFCO) and Jim Neil on reducing structural steel costs;
- Enrique Martinez Romero and Carlos L. Ramos on steel construction in Mexico;
- Jim Rowland (Bethlehem Steel) on industrial buildings;
- Stan Rolfe (University of Kansas), John Bell (Nucor), and Peter Wright (Chaparral Steel Co.) on what structural engineers need to know about fracture mechanics, metallurgy and weldability;
- Michael Engelhardt (University of Texas); Tom Sabol (Englekirk &

Sabol); and Jim Malley (Degenkolb Associates) on research applications of from the Northridge Earthquake;

- R.M. Korol (McMaster University) and Donald Sherman (University of Wisconsin) on new developments in using structural tubes.


In addition, sessions will be held on: constructability issues for contractors; new OSHA legislation and its effect on fabricators and erectors; and effective project specifications for fabricators and engineers. And, of course, the 1995 T.R. Higgins lecture will be presented. As was the case in previous years, continuing education credits (CEUs) will be given for the conference.

In addition to the educational value of the seminars, the conference is an ideal place to meet colleagues as well as many world renowned experts on steel design and fabrication.

Engineers, fabricators and contractors also will benefit from the extensive trade show. In the past, exhibitors have included manufacturers of: fabricating equipment; bolts; fasteners; paints and coatings; joists; and computer software for engineers, fabricators and detailers. This year, more than 60 exhibitors are expected.

Conference co-sponsors include: American Galvanizers Association; AISI; ASCE; AWI, AWS, Canadian Institute of Steel Construction; Construction Industry Institute; Council of American Structural Engineers; Edison Welding Institute; Mexican Institute of Steel Construction; NEA; NISD; SDI; SJI; Steel Plate Fabricators Association; Steel Service Center Institute; Steel Structures Painting Council; Steel Tube Institute of North America; Structural Engineers Association of Texas; and Texas Structural Steel Institute.

TUBING SELECTION



Material Handling Equipment
Mechanical tubing is an integral part of many rack systems.



Shopping Carts
Mechanical tubing can be plated or powder coat painted.
United Terminal/Chicago, IL
Hi-Y 50 is commonly used in construction applications.



Household Furniture
Unique designs can be achieved through the use of mechanical tubing.

The Widest Range of Products... We produce multiple products...structural tubing...HI-Y 50 structural pipe...mechanical tubing. Our size range is so expansive, you can consolidate your purchasing. UNR-Leavitt, the "Tube People", offers professional salespeople...technical services...documented quality assurance. You can also add convenience to the list since UNR-Leavitt products are available through your local steel service center. It's simple...UNR-Leavitt is an industry leader because we put our customers first.



ASTM A513 TYPES I & II
MECHANICAL TUBING • ASTM
A500 GRADES A, B AND C
STRUCTURAL TUBING • HI-Y 50
STRUCTURAL PIPE • HSLA
STRUCTURAL TUBING • ROPS
• RACK TUBING • OCTG
CASING (UNTESTED) • SIZES:
SQUARES AND EQUIVALENT
RECTANGLES: 1/2" X 1/2" TO
10" X 10"; ROUNDS: 3/8" TO
12 3/4" • WALL THICKNESSES:
.018" (26 ga.) TO .500" (1/2").

**UNR
Leavitt**
A Division of UNR Industries, Inc.

GENERAL OFFICES
1717 W. 115th. ST., CHICAGO, IL 60643
PHONE: 312-239-7700 OR
1-800-L-E-A-V-I-T-T
FAX: 312-239-1023

UNR-LEAVITT
CHICAGO, ILLINOIS



UNR-LEAVITT
BLUE ISLAND, ILLINOIS

**Our people
make the
difference**

UNR-LEAVITT
HAMMOND, INDIANA



UNR-LEAVITT
MADISON, MISSISSIPPI

Please circle # 79

Principal Producers Of Structural Shapes

B. Bethlehem Struct. Prod. J. J&L Structural Inc. R. Roanoke Steel U. Nucor Steel
 C. Chaparral Steel M. SMI Steel Inc. S. North Star Steel W. Northwestern Steel & Wire
 F. Florida Steel Corp. N. Nucor-Yamato Steel T. TradeARBED Y. Bayou Steel Corp.
 I. British Steel

Section Weight Per Ft.	Nominal b_f	Producer Code	Section Weight Per Ft.	Nominal b_f	Producer Code
W44 x 230, 262, 290 335	16	T	W27 x 132*	10	I
W40 x 431	16	T	84, 94, 102,		
397*	16	N	114, 129	10	B, I, N, T, W
372	16	T	W24 x 335, 408, 492	12.75	T
362*, 324*	16	N	306	12.75	N
321	16	T	279	12.75	I, N, T
297	16	N	250	12.75	B, I, N
199, 215, 249, 277	16	N, T	229	12.75	B, I, N, T, W
174	16	T	207	12.75	B, N, W
W40 x 278, 331	12	T	104, 117, 131,		
211, 235, 264	12	B, I, T	146, 162, 176, 192	12.75	B, I, N, T, W
183	12	B, I, N, T	W24 x 100*, 120*, 160*	12	N
149, 167	12	B, I, N, T	W24 x 103	9	B, N, W
W36 x 439, 527, 650, 798	16.5	T	84, 94	9	B, I, N, W
393	16.5	B, N, T	68, 76	9	B, C, I, N, W
230, 245, 260, 280,			56*, 61*	9	N
300, 328, 359	16.5	B, I, N, T	W24 x 55, 62	7	B, C, I, N, W
W36 x 256	12	B, I, N	W21 x 182, 201	12.25	I
232	12	B, I, N	101, 111, 122,		
135, 150, 160, 170,			132, 147, 166	12.25	B, I, N, W
182, 194, 210	12	B, I, N, T	W21 x 83, 93	8.25	B, I, N, W
W33 x 387*	15.75	N	62, 68, 73	8.25	B, C, I, N, W
318, 354, 201, 221,			48*, 55*	8.25	N
241, 263, 291	15.75	B, N, T	W21 x 44, 50, 57	6.5	B, C, I, N, W
W33 x 118, 130,			W18 x 258, 283, 311	11	B
141, 152, 169	11.5	B, I, N, T	175, 192, 211, 234	11	B
W30 x 357*, 391	15	N	130, 143, 158	11	B, N, W
261, 292, 326	15	B, I, N, T	W18 x 130*	11	N
284*	15	I	76, 86, 97,		
173, 191, 211, 235	15	B, I, N, T	106, 119	11	B, N, W
W30 x 99, 108, 116, 124,			W18 x 65, 71	7.5	B, I, N, W
132, 148	10.5	B, I, N, T	50, 65, 60	7.5	B, C, I, N, W
W30 x 90	10.5	B, N	W18 x 35, 40, 46	6	B, C, I, N, W
W27 x 539	14	I	W16 x 67, 77, 89, 100	10.25	B, N, W
368	14	I, N	W16 x 57	7	B, I, N, W
336*	14	N	36, 40, 45, 50	7	B, C, I, N, W
307	14	I, N, T	W16 x 26, 31	5.5	B, C, I, N, W
281*	14	N			
258	14	I, N, T			
235	14	I, N			
146, 161, 178,					
194, 217	14	B, I, N, T			

Notes: Maximum lengths of shapes obtained vary with producer, but typically range from 60 ft to 75 ft. Lengths up to 100 ft are available for certain shapes. Please consult individual producers for length requirements.
 * Shapes not currently listed in *Manual of Steel Construction*

Principal Producers Of Structural Shapes

B. Bethlehem Struct. Prod.
C. Chaparral Steel
F. Florida Steel Corp.
I. British Steel

J. J&L Structural Inc.
M. SMI Steel Inc.
N. Nucor-Yamato Steel

R. Roanoke Steel
S. North Star Steel
T. TradeARBED

U. Nucor Steel
W. Northwestern Steel & Wire
Y. Bayou Steel Corp.

Section Weight Per Ft.	Nominal b ₁	Producer Code	Section Weight Per Ft.	Nominal b ₁	Producer Code
W14 x 80816.....		B	W8 x 18, 215.25.....		B, C, N, U, W, Y
455, 500, 550,			W8 x 154.....		B, C, U, W, Y
605, 665, 73016.....		B, I, T	10, 134.....		B, C, M, U, W, Y
370, 390, 42616.....		B, I, T	W6 x 15, 20, 256.....		B, C, I, N, U, W
311, 34216.....		B, I, N, T, W	W6 x 12, 164.....		B, C, U, W, Y
145, 154, 176, 193,			94.....		B, C, J, M, U, W, Y
211, 233, 257, 283 ...16.....		B, I, N, T, W	8.5*4.....		C, J, M, U, Y
W14 x 90, 99,			W5 x 16, 195.....		B, U
109, 120, 13214.5.....		B, I, N, T, W	W4 x 134.....		B, C, M, U, Y
W14 x 8210.....		B, N, W	Section Weight Per Ft.	Producer Code	
7410.....		B, C, N, W	M12 x 10.8, 11.8C, J		
61, 6810.....		B, C, N, W	M12 x 10.0*J		
W14 x 43, 48, 538.....		B, C, N, W	M10 x 8, 9C, J, U		
W14 x 386.75.....		B, I, N, W	M10 x 7.5*J		
30, 346.75.....		B, C, I, N, W	M8 x 6.2*J		
W14 x 22, 265.....		B, C, I, N, W	M8 x 6.5C, J, U		
W12 x 252, 279, 305, 336 ...12.....		B, I	M6 x 3.7*, 4.4J		
210, 23012.....		B, I	M5 x 18.9B		
170, 19012.....		B, I, T, W	M4 x 6*C, U		
65, 72, 79, 87, 96,			S24 x 106, 121B, W		
106, 120, 136, 152 ...12.....		B, I, N, T, W	S24 x 80-100B, W		
W12 x 53, 5810.....		B, C, N, I, W	S20 x 86, 96B, W		
W12 x 508.....		B, C, N, I, W	S20x 66, 75B, W		
40, 458.....		B, C, N, W	S18 x 54.7, 70B, W		
W12 x 26, 30, 356.5.....		B, C, N, W	S15 x 42.9, 50B, W		
W12 x 16, 19, 224.....		B, C, N, W	S12 x 40.8, 50B, W		
144.....		B, C, W	S12 x 35B, W		
W10 x 88, 100, 11210.....		B, I, N, W	S12 x 31.8B, C, W		
49, 54, 60, 68, 7710.....		B, C, I, N, W	S10 x 35B, S		
W10 x 33, 39, 458.....		B, C, N, W	S10 x 25.4B, C, S		
W10 x 22, 26, 305.75.....		B, C, I, N, W	S8 x 18.4, 23C, S		
W10 x 15, 17, 194.....		B, C, I, U, W	S6 x 17.25C, S		
124.....		B, C, U, W	S6 x 12.5C, S, Y		
W8 x 31, 35, 40,			S5 x 10C, Y		
48, 58, 678.....		B, C, I, N, W	S4 x 9.5C		
W8 x 24, 286.5.....		B, C, N, W	S4 x 7.7C, M, Y		
			S3 x 7.5C, J, Y		
			S3 x 5.7C, J, M, Y		
			HP14 x 73, 89, 102, 117B, I, N, W		
			HP12 x 53, 63, 74, 84B, I, N, W		

Notes: Maximum lengths of shapes obtained vary with producer, but typically range from 60 ft to 75 ft. Lengths up to 100 ft are available for certain shapes. Please consult individual producers for length requirements.

* Shapes not currently listed in *Manual of Steel Construction*

Principal Producers Of Structural Shapes

B. Bethlehem Struct. Prod. J. J&L Structural Inc. R. Roanoke Steel U. Nucor Steel
 C. Chaparral Steel M. SMI Steel Inc. S. North Star Steel W. Northwestern Steel & Wire
 F. Florida Steel Corp. N. Nucor-Yamato Steel T. TradeARBED Y. Bayou Steel Corp.
 I. British Steel

Section Weight Per Ft.	Producer Code	Section by Leg Lengths & Thickness	Producer Code
HP10 x 42, 57	B, C, I, N, W	L8 x 8 x 1 1/8	B, T
HP8 x 36	B, C, I, N, W	1	B, S, T
C15 x 33.9, 40, 50	B, N, W	7/8	B, S, T
C12 x 30	B, W	3/4	B, S, T
C12 x 20.7, 25	B, C, S, W	5/8	B, S, T
C10 x 25, 30	B, S, W	9/16	S
C10 x 15.3, 20	B, C, S, U, W	1/2	B, S
C9 x 20	B	L6 x 6 x 1	B, U, Y
C9 x 13.4, 15	B, S	7/8	B, U, Y
C8 x 18.75	S, W, Y	3/4	B, M, U, Y
C8 x 11.5, 13.75	C, M, S, U, W, Y	5/8	B, M, U, Y
C7 x 12.25	S, U, W	9/16	M, U, Y
C7 x 9.8	M, S, U, W	1/2	B, M, S, U, Y
C6 x 13	M, S, U, W, Y	7/16	B, M, U, Y
C6 x 10.5	C, M, S, U, W, Y	3/8	B, M, S, U, Y
C6 x 8.2	C, F, M, U, W, Y	5/16	M, U, Y
C5 x 9	C, M, U, W, Y	1/4	U
C5 x 6.7	C, F, M, U, W, Y	L5 x 5 x 7/8	U, Y
C4 x 5.4, 7.25	C, F, M, U, W, Y	3/4	M, U, Y
C4 x 4.5*	M	5/8	M, U, Y
C3 x 6	M, U, W, Y	1/2	M, U, W, Y
C3 x 4.1, 5	C, F, M, R, U, W, Y	7/16	M, U, Y
C3 x 3.5*	M, R, U	3/8	M, U, W, Y
MC18 x 42.7, 45.8, 51.9, 58	B, N	5/16	M, U, W, Y
MC13 x 31.8, 35, 40, 50	B, N	1/4	U
MC12 x 31, 35, 40, 45, 50	B, N	L4 x 4 x 3/4	M, U, Y
MC12 x 10.6	J, S	5/8	M, U, Y
MC10 x 28.5, 33.6, 41.1	B	1/2	F, M, R, U, W, Y
MC10 x 22, 25	B	7/16	F, M, U, Y
MC10 x 8.4	J, S	3/8	F, M, R, U, W, Y
MC10 x 6.5	J	5/16	F, M, R, U, W, Y
MC9 x 23.9, 25.4	B	1/4	F, M, R, U, W, Y
MC8 x 21.4, 22.8	B, S	L3 1/2 x 3 1/2 x 1/2	F, M, U, W, Y
MC8 x 18.7, 20	B, S	7/16	U, Y
MC8 x 8.5	J, M	3/8	F, M, R, U, W, Y
MC8 x 6.6*	J	5/16	F, M, R, U, W, Y
MC7 x 19.1, 22.7	B	1/4	F, M, R, U, W, Y
MC6 x 18	B	L3 x 3 x 1/2	F, M, U, W, Y
MC6 x 15.1, 16.3	B, S	7/16	U, Y
MC6 x 12	B, S	3/8	F, M, R, S, U, W, Y
MC4 x 13.8*	S	5/16	F, M, R, S, U, W, Y
MC 3 x 7.1*	S	1/4	F, M, R, S, U, W, Y
		3/16	F, M, R, U, W, Y
		L2 1/2 x 2 1/2 x 1/2	F, U, Y
		3/8	F, R, S, U, Y
		5/16	F, R, S, U, Y

Notes: Maximum lengths of shapes obtained vary with producer, but typically range from 60 ft to 75 ft. Lengths up to 100 ft are available for certain shapes. Please consult individual producers for length requirements.

* Shapes not currently listed in *Manual of Steel Construction*

Principal Producers Of Structural Shapes

B. Bethlehem Struct. Prod.
C. Chaparral Steel
F. Florida Steel Corp.
I. British Steel

J. J&L Structural Inc.
M. SMI Steel Inc.
N. Nucor-Yamato Steel

R. Roanoke Steel
S. North Star Steel
T. TradeARBED

U. Nucor Steel
W. Northwestern Steel & Wire
Y. Bayou Steel Corp.

Section by Leg Lengths & Thickness	Producer Code	Section by Leg Lengths & Thickness	Producer Code
		$\frac{3}{8}$F, M, U, W, Y	
		$\frac{5}{16}$F, M, U, W, Y	
		$\frac{1}{4}$F, M, U, W, Y	
L2 x 2 x		$\frac{3}{8}$F, R, S, U, Y	L4 x 3 $\frac{1}{2}$ x
		$\frac{5}{16}$F, R, S, U, Y	$\frac{1}{2}$F, M, U, W
		$\frac{1}{4}$F, R, S, U, Y	$\frac{3}{8}$F, M, R, U, W
		$\frac{3}{16}$F, R, S, U, Y	$\frac{5}{16}$F, M, R, U, W
		$\frac{1}{8}$F, R, S, U, Y	$\frac{1}{4}$F, M, R, U, W
L8 x 6 x		1.....B, S	L4 x 3 x
		$\frac{3}{4}$B, S	$\frac{5}{8}$U, Y
		$\frac{9}{16}$S	$\frac{1}{2}$F, M, U, W, Y
		$\frac{1}{2}$B, S	$\frac{7}{8}$U, Y
		$\frac{7}{16}$B, S	$\frac{3}{16}$F, M, R, U, W, Y
L8 x 4 x		1.....B, S	$\frac{5}{8}$F, M, R, U, W, Y
		$\frac{7}{8}$S	$\frac{1}{4}$F, M, R, U, W, Y
		$\frac{3}{4}$B, S	L3 $\frac{1}{2}$ x 3 x
		$\frac{5}{8}$S	$\frac{1}{2}$U, W
		$\frac{9}{8}$S	$\frac{3}{8}$M, U, W
		$\frac{1}{2}$B, S	$\frac{5}{16}$M, U, W
		$\frac{7}{16}$S	$\frac{1}{4}$M, U, W
L7 x 4 x		$\frac{3}{4}$B, Y	L3 $\frac{1}{2}$ x 2 $\frac{1}{2}$ x
		$\frac{5}{8}$B, Y	$\frac{1}{2}$U
		$\frac{1}{2}$B, S, Y	$\frac{3}{8}$U, W
		$\frac{7}{16}$Y	$\frac{5}{16}$ *.....U, W
		$\frac{3}{8}$B, S, Y	$\frac{1}{4}$U, W
L6 x 4 x		$\frac{7}{8}$B	L3 x 2 $\frac{1}{2}$ x
		$\frac{3}{4}$B, M, S, U, W, Y	$\frac{1}{2}$U, W
		$\frac{5}{8}$B, M, S, U, W, Y	$\frac{3}{8}$U, W
		$\frac{9}{16}$M, S, U, Y	$\frac{5}{16}$U, W, Y
		$\frac{1}{2}$B, M, S, U, W, Y	$\frac{1}{4}$R, U, W
		$\frac{7}{16}$U, Y	$\frac{3}{16}$U
		$\frac{3}{8}$M, S, U, W, Y	L3 x 2 x
		$\frac{5}{16}$M, S, U, W, Y	$\frac{1}{2}$F, U
L6 x 3 $\frac{1}{2}$ x		$\frac{1}{2}$M, U, W, Y	$\frac{3}{5}$F, S, U
		$\frac{3}{8}$M, U, W, Y	$\frac{5}{16}$F, S, U
		$\frac{5}{16}$M, U, W, Y	$\frac{1}{4}$F, R, S, U
L5 x 3 $\frac{1}{2}$ x		$\frac{3}{4}$M, U, Y	$\frac{3}{16}$F, R, U
		$\frac{5}{8}$M, U, W, Y	L2 $\frac{1}{2}$ x 2 x
		$\frac{1}{2}$M, U, W, Y	$\frac{3}{8}$R, S, U
		$\frac{3}{8}$M, U, W, Y	$\frac{5}{16}$S, U
		$\frac{5}{16}$M, U, W, Y	$\frac{1}{4}$R, S, U
		$\frac{1}{4}$M, U, W, Y	$\frac{3}{16}$R, S, U
L5 x 3 x		$\frac{1}{2}$F, M, U, W, Y	
		$\frac{7}{16}$F, Y	

Notes: Maximum lengths of shapes obtained vary with producer, but typically range from 60 ft to 75 ft. Lengths up to 100 ft are available for certain shapes. Please consult individual producers for length requirements.
* Shapes not currently listed in *Manual of Steel Construction*

Principal Producers Of Structural Tubing (TS)

A. Acme Roll Forming Co.	H. Hanna Steel Corp.	N. Hannibal Industries, Inc.	U. UNR- Leavitt, Div. of UNR Inc.
B. Bull Moose Tube Co.	I. Independence Tube Corp.	P. IPSCO Inc.	V. Valmont Industries
C. Copperweld Corp.	J. Vest Inc.	R. Standard Tube Co.	W. Welded Tube Co. of America
D. Dallas Tube & Rollform	L. Laclede Steel Co.	S. Sonco Steel Tube	X. EXLTUBE
E. Eugene Welding Co.	M. Maruichi American Corp.	T. Atlas Tube	Z. Welded Tube of Canada Ltd.

Nominal Size and Thickness	Producer Code	Nominal Size and Thickness	Producer Code
32x32x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*	3x3x ¹ / ₄ , ³ / ₁₆	A,B,C,D,E,H,I,J,M,N,P,R,S,T,U,W,X,Z
30x30x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*	3x3x ¹ / ₈	A,B,C,D,E,H,I,L,M,N,P,R,S,T, U,W,X,Z
28x28x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*	2 ¹ / ₂ x2 ¹ / ₂ x ⁵ / ₁₆	I,S,T
26x26x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*	2 ¹ / ₂ x2 ¹ / ₂ x ¹ / ₄ , ³ / ₁₆	A,B,C,D,E,H,I,J,L,M,N,P,R,S,T, U,W,X,Z
24x24x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*	2 ¹ / ₂ x2 ¹ / ₂ x ¹ / ₈	A,B,C,D,E,H,I,J,L,M,N,P,R,S, T,U,X,W,Z
22x22x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*	2x2x ⁵ / ₁₆	I,S
20x20x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*	2x2x ¹ / ₄	B,C,D,H,I,J,L,M,N,R,S,T,U,W,X,Z
18x18x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*	2x2x ³ / ₁₆ , ¹ / ₈	A,B,C,D,E,H,I,J,L,M,N,P,R,S, T,U,W,X,Z
16x16x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*, W	1 ³ / ₄ x1 ³ / ₄ x ¹ / ₄	H
16x16x ⁵ / ₁₆	W	1 ³ / ₄ x1 ³ / ₄ x ³ / ₁₆	H,Z
14x14x ⁵ / ₈	V*, W	1 ¹ / ₂ x1 ¹ / ₂ x ³ / ₁₆	B,E,H,L,N,P,R,S,U,W,Z
14x14x ¹ / ₂ , ³ / ₈	V*, W	1 ¹ / ₂ x1 ¹ / ₂ x ¹ / ₄	L
14x14x ⁵ / ₁₆	W	32x24x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*
12x12x ⁵ / ₈	B,S,W	30x24x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*
12x12x ¹ / ₂ , ³ / ₈ , ⁵ / ₁₆ , ¹ / ₄	B,S,T,W	28x24x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*
10x10x ⁵ / ₈	B,C,S,W	26x24x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*
10x10x ¹ / ₂ , ³ / ₈ , ⁵ / ₁₆ , ¹ / ₄ , ³ / ₁₆	B,C,P,S,T,U,W	24x22x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*
8x8x ⁵ / ₈	B,C,S,W	22x20x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*
8x8x ¹ / ₂ , ³ / ₈ , ⁵ / ₁₆ , ¹ / ₄ , ³ / ₁₆	B,C,P,S,T,U,W,Z	20x18x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*
7x7x ⁵ / ₈	B,C,S	20x12x ¹ / ₂ , ³ / ₈ , ⁵ / ₁₆	V*, W
7x7x ¹ / ₂ , ³ / ₈ , ⁵ / ₁₆ , ¹ / ₄ , ³ / ₁₆	B,C,P,S,T,U,W,Z	20x8x ⁵ / ₈ , ¹ / ₂ , ³ / ₈	V*, W
6x6x ⁵ / ₈	B,S	18x12x ¹ / ₂ , ³ / ₈	V*
6x6x ¹ / ₂	B,C,P,S,T,U,W,Z	18x6x ¹ / ₂ , ³ / ₈ , ⁵ / ₁₆	B,W
6x6x ³ / ₈ , ⁵ / ₁₆	B,C,D,P,R,S,H,I,J,T,U,W,Z	18x6x ¹ / ₄	B
6x6x ¹ / ₄ , ³ / ₁₆	B,C,D,P,R,S,H,I,J,T,U,W,X,Z	16x12x ¹ / ₂ , ³ / ₈ , ⁵ / ₁₆	V*, W
6x6x ¹ / ₈	B,C,D,S,H,I,J,Z	16x8x ¹ / ₂ , ³ / ₈ , ⁵ / ₁₆	B,W
5 ¹ / ₂ x5 ¹ / ₂ x ³ / ₈ , ⁵ / ₁₆ , ¹ / ₄ , ³ / ₁₆ , ¹ / ₈	B,D,S,H,I,Z	16x4x ¹ / ₂ , ³ / ₈ , ⁵ / ₁₆	B,W
5 ¹ / ₂ x5 ¹ / ₂ x ¹ / ₈	B,S,I,Z	14x12x ¹ / ₂ , ³ / ₈	V*
5x5x ¹ / ₂	B,C,P,R,S,T,U,W,Z	14x10x ¹ / ₂ , ³ / ₈	B,S,W
5x5x ³ / ₈ , ⁵ / ₁₆	B,C,D,H,I,J,P,R,S,T,U,W,Z	14x10x ⁵ / ₁₆	W
5x5x ¹ / ₄ , ³ / ₁₆	B,C,D,H,I,J,M,P,R,S,T,X,U,W,Z	14x6x ⁵ / ₈	B
5x5x ¹ / ₈	B,C,H,I,J,M,P,S,T,Z	14x6x ¹ / ₂ , ³ / ₈ , ⁵ / ₁₆ , ¹ / ₄	B,W
4 ¹ / ₂ x4 ¹ / ₂ x ¹ / ₂	C	14x4x ⁵ / ₈	B,S
4 ¹ / ₂ x4 ¹ / ₂ x ³ / ₈ , ⁵ / ₁₆	T,H,I,P,W,Z	14x4x ¹ / ₂ , ³ / ₈ , ⁵ / ₁₆ , ¹ / ₄	B,S,W
4 ¹ / ₂ x4 ¹ / ₂ x ¹ / ₄ , ³ / ₁₆	B,C,D,H,I,P,T,X,W,Z	14x4x ³ / ₁₆	B,S
4 ¹ / ₂ x4 ¹ / ₂ x ¹ / ₈	B,C,H,I,P,T,X,Z	12x10x ¹ / ₂ , ³ / ₈ , ¹ / ₄	B,S,U
4x4x ¹ / ₂	B,C,P,R,S,T,U,W,Z	12x8x ⁵ / ₈	B,C,S,W
4x4x ³ / ₈ , ⁵ / ₁₆	B,C,D,H,I,J,R,S,T,D,P,U,W,Z	12x8x ¹ / ₂ , ³ / ₈ , ⁵ / ₁₆ , ¹ / ₄	B,C,S,T,W
4x4x ¹ / ₄ , ³ / ₁₆ , ¹ / ₈	B,C,D,E,H,I,J,L,M,N,P,R,S,T, X,U,W,Z	12x8x ³ / ₁₆	B,C,S,U
3 ¹ / ₂ x3 ¹ / ₂ x ⁵ / ₁₆	I,J,P,S,T,U,W,Z	12x6x ⁵ / ₈	B,S
3 ¹ / ₂ x3 ¹ / ₂ x ¹ / ₄ , ³ / ₁₆ , ¹ / ₈	B,C,D,E,H,I,J,L,M,N,P,R,S,T, U,W,X,Z	12x6x ¹ / ₂ , ³ / ₈ , ⁵ / ₁₆ , ¹ / ₄	B,C,S,U,W
3x3x ³ / ₈	C,H	12x6x ³ / ₁₆	B,C,S,U
3x3x ⁵ / ₁₆	C,H,I,J,P,S,T,W,Z		

Notes: *Size is manufactured by Submerged Arc Welding (SAW) process and are not stocked by steel service centers (contact producer for specific requirements). All other sizes are manufactured by Electric Resistance Welding and most are available from steel service centers.

Some manufactures produce a .120 size instead of a ¹/₈; please check with individual manufacturers

Principal Producers Of Structural Tubing (TS)

A. Acme Roll Forming Co.	H. Hanna Steel Corp.	N. Hannibal Industries, Inc.	U. UNR- Leavitt, Div. of UNR Inc.
B. Bull Moose Tube Co.	I. Independence Tube Corp.	P. IPSCO Inc.	V. Valmont Industries
C. Copperweld Corp.	J. Vest Inc.	R. Standard Tube Co.	W. Welded Tube Co. of America
D. Dallas Tube & Rollform	L. Laclede Steel Co.	S. Sonco Steel Tube	X. EXLTUBE
E. Eugene Welding Co.	M. Maruichi American Corp.	T. Atlas Tube	Z. Welded Tube of Canada Ltd.

Nominal Size and Thickness	Producer Code	Nominal Size and Thickness	Producer Code
12x4x ^{5/8}	C, S	6x3x ^{1/2}	C, P, S, T, U, Z
12x4x ^{3/2, 3/2, 5/16, 1/4, 3/16}	B, C, S, U, W, Z	6x3x ^{3/8, 5/16}	B, C, D, H, I, P, S, U, W, Z
12x3 ^{1/2} x ^{3/8, 3/16}	Z	6x3x ^{1/4, 3/16}	B, C, D, H, I, P, R, S, U, W, X, Z
12x3x ^{3/16, 1/4, 3/16}	C, B, Z	6x3x ^{1/8}	B, C, D, H, I, P, R, S, U, X, Z
12x2x ^{1/4, 3/16}	B, S, U, Z	6x2x ^{3/8}	H, S, U, W, Z
10x8x ^{1/2, 3/8, 5/16, 1/4, 3/16}	B, C, S, U, W	6x2x ^{3/16}	B, H, I, J, P, S, T, U, W, Z
10x6x ^{1/2}	B, C, S, T, U, W, Z	6x2x ^{1/4, 3/16}	B, C, D, E, H, I, J, M, N, P, R, S, T, U, W, X, Z
10x6x ^{3/8, 5/16, 1/4, 3/16}	B, C, D, P, S, T, U, W, Z	6x2x ^{1/8}	B, C, D, E, H, I, J, M, N, P, R, S, T, U, W, X, Z
10x5x ^{3/8, 5/16, 1/4, 3/16}	B, C, D, S	5x4x ^{3/8, 5/16}	B, C, I, P, T, W, Z
10x4x ^{1/2}	B, C, P, S, T, U, W, Z	5x4x ^{1/4, 3/16}	B, C, D, I, P, T, W, Z
10x4x ^{3/8, 5/16, 1/4, 3/16}	B, C, D, P, S, T, U, W, Z	5x3x ^{1/2}	C, P, S, T, U
10x3 ^{1/2} x ^{3/16}	Z	5x3x ^{3/8, 5/16}	C, D, H, I, J, P, R, S, T, U, W, Z
10x3x ^{3/8, 5/16, 1/4}	B, D	5x3x ^{1/4, 3/16}	B, C, D, E, H, I, J, M, N, P, R, S, T, U, W, X, Z
10x3x ^{3/16}	B, D, Z	5x3x ^{1/8}	B, C, D, E, H, I, J, M, N, P, R, S, T, U, W, X, Z
10x2x ^{1/2}	Z	5x2x ^{1/4, 3/16}	Z
10x2x ^{3/16}	D, P, S, T, U, W, Z	5x2x ^{3/16}	I, J, P, R, S, T, W
10x2x ^{1/4, 3/16}	B, D, P, S, T, U, W, Z	5x2x ^{1/8, 3/16, 1/8}	B, C, D, E, H, I, J, M, N, P, R, S, T, U, W, X, Z
9x7x ^{1/2, 3/8, 5/16, 1/4, 3/16}	B, C, W, Z	4x3x ^{3/8}	B, S, T
9x5x ^{1/2, 3/8, 5/16, 1/4, 3/16}	B, C, W, Z	4x3x ^{3/16}	I, P, S, W
9x3x ^{1/2}	C	4x3x ^{1/4, 3/16}	B, C, D, H, I, J, E, L, M, N, P, R, S, T, U, W, X, Z
9x3x ^{1/4, 3/8, 5/16}	C, Z	4x3x ^{1/8}	B, C, D, E, H, I, J, L, M, N, P, R, S, T, U, W, X, Z
9x3x ^{1/8, 3/16}	B, C, Z	4x2 ^{1/2} x ^{1/4}	Z
8x6x ^{1/2}	B, C, P, S, T, U, W, Z	4x2x ^{3/8}	H, S, T
8x6x ^{3/8, 5/16, 1/4, 3/16}	B, C, D, P, S, T, U, W, Z	4x2x ^{1/16}	H, I, J, P, S, T, W, Z
8x4x ^{3/8}	B, S	4x2x ^{1/4}	B, C, D, E, H, I, J, L, M, N, P, R, S, T, U, W, X, Z
8x4x ^{1/2}	B, C, P, S, T, U, W, Z	4x2x ^{1/8}	A, B, C, D, E, I, J, L, M, P, R, S, T, U, W, X, Z
8x4x ^{3/4, 5/16}	B, C, D, H, I, J, P, R, S, T, U, W, Z	3 ^{1/2} x2 ^{1/2} x ^{1/4}	Z
8x4x ^{1/4, 3/16}	B, C, D, H, I, P, S, W, X	3x2 ^{1/2} x ^{1/4}	Z
8x4x ^{1/8}	B, C, D, I, J, P, S, Z	3x2x ^{3/16}	I, S, T
8x3x ^{1/2}	C, P, T, U	3x2x ^{1/4}	B, C, D, E, H, I, J, L, M, N, P, R, S, T, U, W, X, Z
8x3x ^{3/8, 5/16}	C, D, H, I, P, U, W, Z	3x2x ^{3/16}	A, C, D, E, I, J, L, M, P, R, S, T, U, W, X, Z
8x3x ^{1/4, 3/16}	B, C, D, H, I, P, S, U, W, Z	3x2x ^{1/8}	S, T, U, W, X
8x3x ^{1/8}	B, C, D, I, P, S, Z	3x2x ^{1/16}	A, B, C, D, E, H, I, J, L, M, N, P, R, S, T, U, W, X, Z
8x2x ^{3/8}	H, J, S, T, U, Z	3 ^{1/2} x2 ^{1/2} x ^{1/4}	Z
8x2x ^{3/16}	H, I, J, P, S, T, U, W, Z	3x2 ^{1/2} x ^{1/4}	Z
8x2x ^{1/4, 3/16}	B, D, H, I, J, P, S, T, U, W, Z	3x2x ^{3/16}	I, S, T
8x2x ^{1/8}	B, D, I, J, P, S, T, Z	3x2x ^{1/4}	B, C, D, E, H, I, J, L, M, N, P, R, S, T, U, W, X, Z
7x5x ^{1/2}	B, C, P, S, T, U, W, Z	3x2x ^{3/16}	A, C, D, E, I, J, L, M, P, R, S, T, U, W, X, Z
7x5x ^{3/4, 5/16, 1/4, 3/16}	B, C, D, H, I, P, R, S, T, U, W, Z	3x2x ^{1/8}	S, T, U, W, X
7x5x ^{1/8}	B, C, I, P, S, T, X, Z	3x2x ^{1/16}	A, B, C, D, E, H, I, J, L, M, N, P, R, S, T, U, W, X, Z
7x4x ^{3/8, 5/16, 1/4, 3/16}	B, C, D, H, I, P, S, U, W, Z	3x1 ^{1/2} x ^{3/16, 1/8}	C, E, I, U, W
7x4x ^{1/8}	C, I, P, S, Z	3x1 ^{1/2} x ^{1/4}	I, Z
7x3x ^{3/8, 5/16}	B, C, D, H, I, P, S, W, Z	2 ^{1/2} x1 ^{1/2} x ^{1/4}	A, B, C, E, I, S, U, X
7x3x ^{1/4, 3/16}	B, C, D, H, I, P, S, W, X, Z	2 ^{1/2} x1 ^{1/2} x ^{3/16}	B, C, E, H, I, R, S, U, X, Z
7x3x ^{1/8}	C, D, H, I, P, S, Z	2x1 ^{1/2} x ^{3/16}	Z
6x4x ^{1/2}	B, C, P, S, T, U, W, Z	2x1x ^{3/16}	Z
6x4x ^{3/8, 5/16}	B, C, D, H, I, J, P, R, S, T, U, W, Z	1 ^{1/2} x1 ^{1/2} x ^{1/4}	H, L
6x4x ^{1/4, 3/16}	B, C, D, H, I, J, M, P, R, S, T, U, W, X, Z		
6x4x ^{1/8}	B, C, D, I, J, P, S, T, V, X, Z		

Notes: *Size is manufactured by Submerged Arc Welding (SAW) process and are not stocked by steel service centers (contact producer for specific requirements). All other sizes are manufactured by Electric Resistance Welding and most are available from steel service centers.

Some manufactures produce a .120 size instead of a 1/8; please check with individual manufacturers

Principal Producers Of Steel Pipe (P)

A. Acme Roll Forming Co.
B. Bull Moose Tube Co.
C. Copperweld Corp.
D. Dallas Tube & Rollform
E. Eugene Welding Co.

H. Hanna Steel Corp.
I. Independence Tube Corp.
J. Vest Inc.
L. Laclede Steel Co.
M. Maruichi American Corp.

N. Hannibal Industries, Inc.
P. IPSCO Inc.
R. Standard Tube Co.
S. Sonco Steel Tube
T. Atlas Tube

U. UNR- Leavitt, Div. of UNR Inc.
V. Valmont Industries
W. Welded Tube Co. of America
X. EXLTUBE
Z. Welded Tube of Canada Ltd.

Nominal Size and Thickness	Producer Code	Nominal Size and Thickness	Producer Code
20x.500, .375	P ^a , W	6.125x.500, .375, .312, .250, .188	C
20x.250	P ^a	6x.500	S, Z
18x.500, .375	P ^a , W	6x.375, .312	H, R, S, Z
18x.250	P ^a	6x.280	H, R, S, X, Z
16x.500	P ^a , W	6x.250, .188	H, R, S, Z
16x.375	P ^a , W	6x.125	H, Z
16x.250	P	5.563x.500	Z
16x.188	P	5.563x.375	P
14x.500	P, W	5.563x.258	P, R, W, X, Z
14x.438	P	5.563x.188	
14x.375	P, W	5.563x.134	P, R, Z
14x.250, .188	P	5.5x.375, .258	U, Z
12.75x.500	P, W	5x.500, .375, .312	C, P, T, Z
12.75x.406	P	5x.258	C, P, R, T, U, X, Z
12.75x.375	P, W	5x.250, .188	C, H, L, P, R, S,
12.75x.188, .125	P		T, U, Z
12.5x.625, .500, .375, .312, .250, .188	C	5x.125	C, H, L ^a , P, R, S,
11.25x.625, .500, .375, .312, .250, .188	C		T, U, Z
10.75x.500, .365, .250	P, W, Z	4.5x.337	Z
10x.625	C	4.5x.237, .188	C, H, L ^a , P, R, S,
10x.500, .375, .312	C, Z		U, W, X, Z
10x.250, .188	C, Z	4.5x.125	C, H, L ^a , P,
10x.125	V		R, S, U, Z
9.625x.500	C, U, Z	4x.337	H, R, S, U
9.625x.375, .312, .250, .188	C, P, U, Z	4x.250, .188	C, H, R, S, U, Z
8.75x.500, .375, .312, .250, .188	C	4x.237	C, H, R, S, U, Z
8.625x.500	P, S, U, Z	4x.125	C, H, R, S, U, Z
8.625x.375	P, S, U, Z	3.5x.313	Z
8.625x.322	P, S, U, W, Z	3.5x.300	H, P, S, X, Z
8.625x.250, .188	P, S, U, Z	3.5x.250, .203, .188, .125	H, P, S, U, Z
8.625x.125	P, S	3.5x.216	H, P, R, S, U, X, Z
7.625x.125	Z	3x.250, .203, .188, .152	H, L, R, S, U, Z
7.5x.500, .375, .312, .250, .188	C, R	3x.300	S, X, Z
7x.500	C, P, U, Z	3x.216	R, S, U, X, Z
7x.375, .312, .250	C, H, P, R, S, U, Z	3x.120, .134	Z
7x.188	C, H, P, R, S, U, Z	2.875x.250	L ^a , P, U, Z
7x.125	C, P, Z	2.875x.203	L ^a , P, U, W, Z
6.875x.500, .375, .312, .250, .188	C	2.875x.188, .125	L ^a , P, U, Z
6.625x.500, .432	P, U, Z	2.375x.250, .218, .188	H, L, P, S, Z
6.625.375, .312	H, P, R, U, Z	2.375x.154	H, L, P, S, U,
6.625x.280	H, P, R, U, W, X, Z		W, X, Z
6.625x.250, .188	H, P, R, U, W, X, Z	2.375x.125	H, P, R, S,
6.625x.125	P, Z		U, Z

Notes: ^aSize is manufactured by Submerged Arc Welding (SAW) process and are not stocked by steel service centers (contact producer for specific requirements). All other sizes are manufactured by Electric Resistance Welding and most are available from steel service centers.

Some manufactures produce a .120 size instead of a .125; please check with individual manufacturers

Structural Steel Shape Producers

Bayou Steel Corp. P.O. Box 5000 Laplace, LA 70068 (800) 535-7692	Chaparral Steel Co. 300 Ward Road Midlothian, TX 76065-9501 (800) 529-7979	Northwestern Steel & Wire Co. 121 Wallace St. P.O. Box 618 Sterling, IL 61081-0618 (800) 793-2200	Nucor-Yamato Steel P.O. Box 1228 Blytheville, AR 72316 (800) 289-6977
Bethlehem Struct. Prod. Corp. 501 East Third St. Bethlehem, PA 18016-7699 (800) 633-0482	Florida Steel Corp. P.O. Box 31328 Tampa, FL 33631 (800) 237-0230	North Star Steel Co. 1380 Corporate Cntr. Curve P.O. Box 21620 Eagan, MN 55121-0620	Roanoke Electric Steel Corp. P.O. Box 13948 Roanoke, VA 24038 (800) 753-3532
British Steel Inc. 475 N. Martingale Rd. #400 Schaumburg, IL 60173 (800) 542-6244	J&L Structural Inc. 111 Station St. Aliquippa, PA 15001 (412) 378-6490	Nucor Steel P.O. Box 126 Jewett, TX 75846 (800) 527-6445	SMI Steel, Inc. 101 South 50th St. Birmingham, AL 35232 (800) 621-0262
			TradeARBED 825 Third Ave. New York, NY 10022 (212) 486-9890

Structural Tube Producers

ACME Roll Forming Co.* 812 North Beck St. Sebewaing, MI 48759-1120 (800) 937-8823	Eugene Welding Co.* P.O. Box 249 Marysville, MI 48040 (800) 336-3926	IPSCO Steel, Inc. P.O. Box 1670, Armour Rd. Regina, Saskatchewan S4P 3C7 CANADA (416) 271-2312	UNR-Leavitt, Div. of UNR Industries, Inc.* 1717 West 115th St. Chicago, IL 60643-4399 (800) 532-8488
Atlas Tube* 200 Clark St. Harrow, Ontario, NOR 1G0 CANADA (519) 738-3541	EXLTUBE 905 Atlantic N. Kansas City, MO 64116 (800) 892-8823	Laclede Steel Co.* One Metropolitan Square St. Louis, MO 63102-2739 (314) 425-1461	Valmont Industries, Inc.* (Structural Tube Division) 801 North Xanthus P.O. Box 2620 Tulsa, OK 74101 (800) 331-3002
Bull Moose Tube Company* 1819 Clarkson Road, Suite 100 Chesterfield, MO 63017-5040 (800) 325-4467	Hanna Steel Corp.* 3812 Commerce Ave. P.O. Box 558 Fairfield, AL 35064 (800) 633-8252	Maruichi American Corp.* 11529 S. Greenstone Ave. Santa Fe Springs, CA 90670 (310) 946-1881	Vest Incorporated* 6023 Alcoa Ave. Los Angeles, CA 90058 (213) 581-8823
Copperweld Corporation* 4 Gateway Center, Ste. 2200 Pittsburgh, PA 15522 (412) 263-3200	Hannibal Industries, Inc.* P.O. Box 58814 Los Angeles, CA 90058 (213) 588-4261	Sonco Steel Tube* 14 Holtby Ave. Brampton, Ontario L6S 2M3 CANADA (800) 268-3005	Welded Tube Co. of America* 1855 E. 122nd St. Chicago, IL 60633 (800) 733-5683
Dallas Tube & Rollform P.O. Box 540873 Dallas, TX 75354-0873 (214) 556-0234	Independence Tube Corp.* 6226 W. 74th St. Chicago, IL 60638-6196 (708) 496-0380	Standard Tube Company* P.O. Box 430 Woodstock, Ontario N4S 7Y6 (519) 537-6671	Welded Tube of Canada, Ltd.* 111 Rayette Road Concord, Ontario L4K 2E9 CANADA (800) 837-3616

* Member of the Steel Tube Institute of North America, 8500 Station St., Suite 270, Mentor, OH 44060 (216) 974-6990

Looking For ANSWERS?

- What is the compatibility of spray-applied fireproofing with shop primers?see page 1-11
- When must expansion joints be provided in steel structures?see page 1-13
- Where can I find a good primer on LRFD?see section 2
- How are single-angle struts designed?see page 3-104
- How can I design to eliminate floor deflection and vibration problems?see page 4-207
- What is the difference between snug-tightened and fully tensioned bolts?see page 8-12
- How can the engineer-of-record determine if bolts are suitable for re-use?see page 8-19
- When can bolts and welds in the same connection be considered to share load?see page 8-211
- What is the difference between a shim and a filler?see page 8-327
- How can I avoid problems with double connections?see page 9-9
- How is eccentricity considered in the design of shear splices?see page 9-179
- Why are extended end-plate connections limited to static loading only?see page 10-21
- When are stiffeners required at beam-to-column flange moment connections?see page 10-35
- How are forces transferred in diagonal bracing connections?see page 11-19
- What is the most efficient reinforcement detail for beams with web penetrations?see page 12-11

They're in here →

Call 312/670-2400
Two-volume set only \$132
(\$99 for AISC members)



2nd Edition LRFD
Manual of Steel Construction



Setting Standards For Over 70 Years

RENOVATION REMEDIES

STRUCTURAL HEADACHES

Renovating a vintage 1917 concrete building with planar steel frames allowed Boston University to modernize a laboratory while adding additional space



By Zareh B. Gregorian, P.E.,
and Garen B. Gregorian

RATHER THAN CONSTRUCTING A NEW FACILITY, BOSTON UNIVERSITY OPTED TO BUILD its Cantor Smith Laboratory by reconfiguring and modernizing an existing three-story concrete building. Built in 1917, the building had previously housed a library on its first and second floors with research space on its upper floor. To increase the work space for the tenants, the university shifted the existing library space on the second floor to the basement and added new mechanical space on the roof to house the equipment displaced from the basement.


Complicating the project, however, was the previously unknown poor structural condition of the existing building and the need to fit construction into an academic schedule requiring all work to be done between the end of the spring session and the start of the fall term.

EXISTING CONDITIONS

The existing building was an SMI (Smulski) flat slab system with a circular reinforcing pattern, which was a popular design in the northeast at the time the building was originally designed. In this system, each of the five panels (one on each face of the column and one at the center) act as independent elements, with circular reinforcement installed at each panel and with minimal continuity between panels provided by reinforcing bars. Due to the discontinuous pattern



Several techniques were used to repair and strengthen the existing concrete frame. Shown above are chemically anchored dog stitches. Shown at top is a newly mounted steel beam.



of the reinforcing, poor quality of the concrete, and bad construction, major cracks had developed at the third floor slab. In addition, large deflections—in the order of 7 in.—had occurred, and large cracks had developed in the roof slab.

The design was so poor that sometime in the past a pair of 24-in. steel beams had been placed above the roof to help overcome the sagging of the roof slab. The beams span diagonally between columns and were used to hang the slab by rods.

ADDING A NEW FLOOR

The new mechanical level was framed in steel to minimize weight requirements and to speed the construction. However, construction of the new mechanical level required the removal of the two existing diagonal beams from the roof and repairing the cracked and sagging slabs.

Several options were considered for remedying the problem of the sagging slab, including removing the deteriorated panels. However, that would have required shoring of the structure and the removal and replacement of at least three 26-ft. x 28-ft. bays at various locations—all while the lower floors were in operation.

Since the building is located in a crowded institutional area, heavy cutting equipment, which would generate excessive noise, could not be used.

After reviewing various options with the project team, which included Paul McGowan, senior vice president and design principal with Cannon, Youngjo Sul, senior associate with Cannon, Paul Rinaldi, director of the office of space management at Boston University, and Gus Stathis, director of project management at Boston University, the decision was made to repair

damaged portions of the slabs rather than replacing entire bays. Structural engineer on the project was Gregorian Engineers, Belmont, MA.

In addition to the corner slab that was hung from the steel beams, two additional bays were severely cracked and sagging and in need of immediate repair. The solution was to install a grid of steel beams to support the sagging slabs. The grid consists of a W18x50 member spanning diagonally between two columns, with a W18x35 member picking up the additional load of the slab. In addition some W8x10 tie members were utilized. The beams were tied to the column heads by expansion anchors. Special details were developed to provide connections to the drop panels and capitals.

The support frames were designed to support the weight of the slab and the live load.



Shown above is the grid of new steel beams after fire proofing was applied.

Auxiliary members were installed between main frame members under cracks to reduce the acting span of the existing slabs. The design utilized one W18x50 member framing diagonally from column-to-column and

two W18x35 members framing into four W14x38 beams connecting four concrete columns at the corner of the structure. Six W8x10 intermediate short span members frame between main steel members for additional support. Shear connector anchor bolts are used to connect new steel girders to concrete columns, capitals and drop panels.

In areas with excessive sagging, structural T sections were cut at the web and welded to the top of the steel members to shape the beam in the form of the deflected slab. Non-shrink grout was packed between the top of the steel beams and the bottom of the slab to provide load transfer from the slab to the steel frame and finally to the concrete columns.

In other roof slab and third floor slab areas with minor cracks, pressure injected epoxy and chemically anchored dog stitches were used to prevent the

For the BEST in Bridge Software . . .

DESCUS DESIGN & ANALYSIS CURVED BRIDGES

- ◆ Curved & Straight Bridge Systems
- ◆ Influence Surface Approach
- ◆ "T" and BOX Girder Sections
- ◆ Latest AASHTO - LFD & WSD
- ◆ METRIC and English Units
- ◆ Girder Optimization
- ◆ Auto MESH Generation
- ◆ Auto RATING FACTORS - Inventory Operating, Posting, Special Vehicle
- ◆ Complex Geom. - Skewed, Bifurcated
- ◆ Pouring Sequence Analysis Available
- ◆ PC License or Lease, Timesharing
- ◆ Menu-Driven/CAD-Like Features
- ◆ Fast Running (Minutes)

MERLIN DASH DESIGN OF STRAIGHT HIGHWAY BRIDGES

- ◆ AASHTO - WSD, LFD (LRFD Analysis)
- ◆ Analysis, Rating, Code Check
- ◆ Optimization by Cost or Weight
- ◆ Auto Live Load - AASHTO and Multiple User Defined Concurrent Live Load
- ◆ Auto RATING FACTORS - Inventory, Operating, Posting, Special Vehicles
- ◆ METRIC/English Conversion
- ◆ Deck Pouring Sequence Analysis
- ◆ Haunched Web, Hybrid, Composite
- ◆ Continuous Spans, Support Restraints
- ◆ Graphics - Moment, Shear, Camber Allow/Actual Stress & Ranges
- ◆ Menu Input - Very Friendly

SABRE SIGN BRIDGE ANALYSIS/DESIGN

- ◆ Most Types - Tri-Chord, Box Chord Single/Double Cantilever, Other
- ◆ Analysis - Moment, Shear, Torque Displacement, Reaction, Stress
- ◆ Design - Splices, Base Plates
- ◆ Auto Load Cases - Wind (shielding), Ice, DL, User Defined Loads
- ◆ Pull Down Menu/CAD-Like Features
- ◆ Latest AASHTO Code Checking

TRAP TRUSS RATING AND ANALYSIS

- ◆ NEW - AASHTO LRFD and LFD Spec.
- ◆ Cable Member Prestressing
- ◆ Most Truss Types Considered
- ◆ Analysis, Design, Rating, Rehabilitation
- ◆ Auto RATING FACTORS - Inventory, Operating, Posting, Special Vehicles
- ◆ Automatic Group Load Combinations
- ◆ Simple or Continuous to 6 Spans
- ◆ Pull-Down Menu/CAD-Like Features

Available Exclusively Thru:

OPTI-MATE, INC.

P.O. Box 9097 • Dept. A
Bethlehem, PA 18018

Tel 610-867-4077
Fax 610-865-1030

Free Trial...
FULL PROGRAM
(No Deposit)

Please circle # 53

GRINDER SOFTWARE COMPANY

MATERIAL ESTIMATING FOR STEEL FABRICATORS

- ✓ Accomplish in 3 hours time what used to take 8 hours with pencil and paper.
- ✓ Keep material waste to the absolute minimum using our unique length optimizing process.
- ✓ Produces 12 precise, easy to read reports for use by the shop and office.
- ✓ Handles ferrous and non-ferrous metals, fasteners, hardware, misc. items and assembled units. Also tracks shop and field labor.
- ✓ Interfaces with the SteelCad™ International detailing software.
- ✓ A "Competitive Upgrade" is available.
- ✓ "Test Drive" our fully functional demo for 30 days and start saving today.

1774 Rose Valley Road
P.O. Box 431
Kelso, WA 98626

Tel 800 677-4474
Fax 206 577-4474

COMPUTER SOFTWARE FOR SUCCESSFUL STEEL FABRICATORS

Please circle # 57

existing cracks from further propagation. Bent and threaded rods were installed in pre-drilled holes from underneath the slab and anchored to the slab by chemical epoxies. To select the diameter of the dog stitches and the required penetration lengths and spacing, the Smulski system was analyzed to obtain the pattern of bending moments and the resulting tensile forces in various parts of the slabs in crack locations.

RAPID ERECTION

It took two skilled steel erectors only one day to install the frames for each panel. Fabricator and erector on the project was AISC-member American Architectural Iron Co. General contractor was Walsh Brothers of Cambridge, MA. The epoxy injection and grouting took an additional day, which brought total installation time to less than one week. Accordingly, the project was completed in September in accordance with the university's schedule and requirements.

In contrast, the concrete alternative to using steel frames would have resulted in the cutting and removal of huge areas of the existing structure, column reinforcement, and the installation of 11 new concrete boundary beams and new slabs with the requisite welding of new reinforcement bars to the existing slabs. Finally, placing new concrete would have required at least three weeks for the concrete to obtain the required strength. In short, the process would have been expensive, noisy, time consuming, and would have required extensive shoring and disturbance to the on-going operation of the building tenants.

Zareh Gregorian, P.E., is principal and Garen B. Gregorian is project engineer for Zareh B. Gregorian Consulting Structural Engineers in Belmont, MA.


A new addition to the Design Advisor family:

FLOOR VIBRATIONS

An Expert System to Help the Designer

Six Tolerance Criteria to Choose From:

Murray - - - - -	Office/Residential Environments	
Modified Reiher-Meister - - - - -	Office/Residential Environments	
Wiss-Parmelee - - - - -	Office/Residential Environments	
Canadian Standards Association - - - - -	Walking Vibrations	
Ellingwood and Tallin - - - - -	Commercial Environments	
Allen	} With	Offices
Aerobics		Residential
Dancing		Dining
Lively Concert		Weightlifting
Sports Event		



To order send P.O., check or money order for \$250 plus \$10 S&H to:

Structural Engineers Inc.
537 Wisteria Drive
Radford VA 24141

Voice: (703) 731-3330

FAX: (703) 639-0713

Site licenses are available

Please circle # 78

WHITEFAB INC.

BIRMINGHAM
ALABAMA

IN ADDITION TO ANGLE, RAIL, PIPE, CHANNEL, AND BEAM ROLLING CAPABILITIES, WE ROLL TUBES, CHANNELS, AND BEAMS THE HARD WAY.

Phone (205)791-2011 FAX (205)791-0500

Please circle # 55



19600

THIS IS GOING TO BE THE MOST POPULAR CONSTRUCTION SIGHT IN AMERICA.

Nucor-Yamato Steel is reshaping the way America sees construction. With an expanded mill that can supply

more structural steel than any mill in the Western Hemisphere.

THE BIGGEST MILL And not only more steel, but a broader product line with beams up to 40 inches deep. Perhaps best of all, we are a low cost producer. It all adds up to just one thing: talk to Nucor-Yamato before you decide to build your next project.

AVAILABILITY With 1.6 million tons behind us, nothing can stop our availability and on-time delivery by rail or truck or barge on a wide range of products. In fact, we can offer high

strength steel at little or no more cost than standard ASTM A36 beams.

QUALITY Nucor-Yamato is a state-

of-the-art mill, including electric arc and ladle metallurgy furnaces, continuous beam blank casting and high performance

rolling mills designed to produce stock and other lengths for all our customers. All our steel is low carbon and fine grain with superior toughness and surface quality that offers both weldability and improved corrosion resistance.

LOW COST PRODUCER Perhaps best of all, it's produced cost effectively for some of the most competitive prices you'll ever see. And if you're in the construction business these days, that's a sight for sore eyes.

Contact Nucor-Yamato Steel early in your next project at 800/289-6977, FAX 501/763-9107; or write to us at PO Box 1228, Blytheville, Arkansas, 72316.

Structural shapes from W6 X 15 to W40 X 297
Standard sections including C15 X 33.9-50, MC 12 X 31-50, MC 13 X 31.8-50 and MC 18 X 42.7-58
H-Piling ranging from HP 8 X 36 to HP 14 X 117
Grades include ABS Grades A, B, AH32, AH36; ASTM A36; ASTM A572 Grade 50; ASTM A588 ("weathering steel"); ASTM A709 (AASHTO M270 equivalents); as well as CSA 40.21 Grade 44W

NUCOR - YAMATO STEEL COMPANY

Please circle # 39

EXTERNAL BRACING PROVIDES SEISMIC SUPPORT

The retrofit of a 1960s university building was economically accomplished with a system of external steel braces

By Peter A. Timler, P.E., and
John G. Sherstobitoff



An external steel frame was used to bring this laboratory building up to current seismic code level.

THE INFLUENCE OF CALIFORNIA'S EARTHQUAKES EXTENDS BEYOND THE STATE'S, and indeed the U.S.'s, border. After the Loma Prieta earthquake of 1989, the government of British Columbia—the Canadian province due north of California—began evaluating and upgrading many of its older and more vulnerable structures. Recently, the primary laboratory teaching facility at the British Columbia Institute of Technology (BCIT) was upgraded to bring it to 100% of current code requirements.



Objectives for the renovation of the building, located in the Vancouver suburb of Burnaby, included: minimizing costs; completing the project within a three-month period during the summer of 1993; minimizing disruption to mechanical and electrical systems, since all adjacent buildings shared the system and were to be fully occupied and operational during the construction period; and maximizing the aesthetics of the finished renovation.

The existing building was constructed in 1962. However, because it was constructed under federal jurisdiction, it was exempted from local building codes and it is unknown whether it was designed to meet the existing standards. The main building is a four-story structure consisting of 5-in. or 6-in. lightweight concrete floor slabs sup-

ported on steel beams and concrete encased steel columns. The 361-ft. by 75-ft. building is rectangular in plan with an inter-story height of 12-ft. 9-in. A light steel-framed penthouse covers approximately 50% of the roof floor plan area. The building was connected with neighboring buildings to form a courtyard. The existing lateral load system consisted of four lightly reinforced concrete stairwells well distributed along the building's length. Evaluation of the structural details of the existing building indicated a structure with very nominal capacity because of the lack of specific detailing for ductile behavior. The elastic capacity of various elements ranged from 20% to 40% relative to current code requirements.

Initially, the renovation called for incorporating 20 new internal reinforced concrete shear walls at a cost of \$3.3M CDN, excluding any non-structural seismic restraint or any improvements within the building envelope. However, after careful consideration, the designers—in consultation with the building's users—created a scheme combining external steel bracing with external shear walls. In addition to reducing the cost of the renovation by half, it created a striking visual concept for an "Institute of Technology" that appealed to the client. A final advantage was the some of the elements of this project could be incorporated into a future planned retrofit of the adjacent buildings in the complex.

The renovation was accomplished under the CAN/CSA-S16.1-M89 (S16.1) Limit States Design of Steel Structures code, the first Canadian code that specifically addressed the ductility requirements of steel structures in seismic design. Each steel lateral load-resisting system is addressed with compatible design rules commensurate with the force modification factor R. The R value is relative to the system's capacity to absorb ener-



gy by undergoing inelastic deformations. The code recognizes overstrength provision (or the capacity design approach), in which brace sizes selected for reasons other than actual strength or stability thereby exhibit resistances greater than those required to carry the seismic loads and therefore impose potentially larger connection design forces because of their increased reserve in strength. For this building, a calculated design base shear equivalent to 31% of the weight of the struc-

ture was dictated by the code.

The code also contains ductility requirements for braced frames expected to undergo intense cyclic loading. The code recognizes the need for redundancy in opposing directions per planer frame. Redundancy restricts dramatic changes in overall torsional resistance that would otherwise lead to subsequent catastrophic loss in shear capacity as compression braces buckle. Additionally, controlling local buckling of members is emphasized by the imposition of


A Quick Quiz For Structural Engineers

The more a computer program costs, the better it is. TRUE FALSE

A program that solves complex, difficult problems must be complex and difficult to use. TRUE FALSE

Structural engineering software can never be fun to use. TRUE FALSE

If you answered *TRUE* to any of the above, or you would like to know more about a truly innovative software program, call us!



RISA-2D

Your complete solution for
frames, trusses, beams,
shear walls and much more!



26212 Dimension Drive, Suite 200
Lake Forest, CA 92630
1-800-332-7472

Please circle # 40




Mound Architectural

Fabricators of Quality Railing and
other Decorative Metal Products

Pricing available for standard products.
NO CHARGE FOR QUOTATIONS
on most custom projects.

Standard picket rail from \$17.00 a lineal foot.

940 Holman Ave., Monroe, OH 45050
513-422-0584 513-422-5184 (FAX)




Please circle # 49

more severe width-thickness ratios than Class 1 limitations. To maintain reasonable levels of energy absorption while undergoing plastic bending during overall buckling conditions, diagonal bracing members also must meet stricter slenderness ratios. As significant reserves in strength, which can easily be drawn upon through capacity response of the frame, are likely to exist in the bracing members themselves, connections are designed for higher load levels, i.e., twice those obtained from elastic analysis. Coupled with the braces overall energy dissipation requirements through out-of-plane buckling, gusset plates must be detailed to avoid brittle failures.

EXTERNAL BRACING

A ductile-bracing frame scheme with an R value of 3.0 was selected for several reasons. The ductility rating of this system would approach equivalence with that of the proposed reinforced concrete end walls, which have an R value of 3.5—an important consideration for retrofit performance. Also, overall member force levels would be reduced significantly; 33% over nominally ductile and 50% over non-ductile steel-reinforced framing schemes because of increased deformational characteristics. However, greater demand, required in the design and detailing of connections, would ensure the necessary ductile behavior. Reducing the force levels was an important consideration because of the long plan dimension in the north-south direction. As a result, an unusually large torsional component had to be added to the east-west oriented code earthquake base shear.

As a result of these considerations, along with architectural and erection considerations, the reinforcement system was designed with wide flange beam and column grillage incorporating hollow structural steel bracing. To reduce the size of the



bracing members, a fully braced system was used on the west face of the main building, with near fully braced systems on the west and east faces of the north

and south wing structures, respectively. The near fully braced systems allowed unrestricted student and faculty access to the courtyard.

AESTHETIC CONCERNS

Unlike an internal strengthening system, great care must be taken to visually integrate an

Automatic preheating or manual – how do you decide?

Once you compare, the choice is obvious. Automatic electrical resistance preheating helps control project costs by:


Increasing welder productivity

Labor costs are reduced because components are always ready for welding. Your personnel are freed from time-consuming manual preheating chores. The electrical equipment creates a safe working environment.

Avoiding expensive rework

Uniform maintenance of minimum temperature controls two common causes of rework – cracking and hydrogen formation.

Request our FREE literature and information on our successful Northridge earthquake projects.



Typical preheat layout for underside of column-beam weld joint




COOPERHEAT

CORPORATE HEADQUARTERS

1021 Centennial Avenue, Piscataway, NJ 08854
Toll Free: 800-526-4233
Tel: 908-981-0800 • Fax: 908-981-0850

Please circle # 56

UPDATED COMPREHENSIVE DIAPHRAGM DESIGN MANUAL



SECOND EDITION

A reference source that contains the answers to all of your questions!

FOR PRACTICING ENGINEERS & ARCHITECTS!

Organized For Easy Use/Explicitly Illustrated

EASY REFERENCE TO

- Diaphragm Strength
- Diaphragm Stiffness
- Connections
- Concrete Filled Diaphragms
- 62 Pages Filled with Shear Diaphragm Examples
- Complete Guide to Symbols and References
- Complete set of Load Tables for Typical Panel Configurations and Connector Types
- Typical Fastener Layout
- Warping Factor Development
- D-Values for Warping



DON'T DELAY—ORDER YOURS TODAY!

Send checks; postal, world money orders, drafts, in U.S. currency.

Quantity

_____ 2ND. EDITION DIAPHRAGM DESIGN MANUAL, \$55.00 ea.	_____
_____ 1st. Edition Diaphragm Design Manual, \$30.00 ea.	_____
_____ Steel Deck Design Manual, \$19.75 ea.	_____
_____ US Currency Total	_____
_____ Out of USA surcharge, 10%	_____
_____ Add on for Airmail	_____
_____ Total Enclosed	_____

STEEL DECK INSTITUTE, INC.

P.O. BOX 9506, CANTON, OHIO 44711 ■ (216) 493-7886

Please circle # 77

external bracing system with the existing structure. Particularly important is to minimize window coverage. In addition to visual concerns, an erection plan was needed that would allow the use of a small mobile crane capable of entering the courtyard through a 9-ft. vertical clearance breezeway.

Selection of a framing connection system was based on the erection sequence of the members and on minimization of field welding for quality control. As a result, end-plate connections on beams with bracing gusset hardware were chosen. The gusset plates, which would receive the slotted HSS braces prepared with angle end clips, would enable quick erection bolting followed by brace-to-gusset field welding. To meet architectural requirements, a series of scalloped gusset plates were developed. The detailed radii of these plates were relative to each braced connection coinciding at the joint and other local joints.

The new external bracing system was connected directly to the floor diaphragms of the existing structure. Connection design force levels of the frames to the building were limited to two times the anticipated earthquake shear equally distributed to each connector location. When this force level presented conditions in which an unreasonable number of anchors were necessary and their clustering interfered with their efficiency, a total floor shear force was calculated on the basis of the buckling capacity of every brace associated with the floor level under consideration. Because of the optimization of the bracing sizes for the frames, this overstrength limitation ranged between 1.3 and 1.7 of the design earthquake shears.

The exterior finish of the main building differed from the two wing buildings, but a similar connection, utilizing T-sections or angles, was provided.

The main building was finished with an exposed aggregate



stucco. A full length band of connection zones was sawcut and lightly jack-hammered to expose the formed concrete surface of the upstand beam at the diaphragm level. A $\frac{3}{16}$ -in.-thick industrial grade neoprene strip of durometer hardness 50 was installed behind the flanges to accommodate some of the finish variations from the original forming. A flashing was incorporated to provide waterproofing. Prefabricated T-sections welded between the flanges of the beam facilitated connection via its web to the unit previously secured to the building. Galvanized shims made up erection discrepancies between the connector units secured to the face of the building and the beams of the frames. Adhesive concrete anchors bolted the connector units directly to the building.


Horizontal reactions from the slabs at each floor level and the roof were transferred through drag struts to the walls along the north and south wings of the complex. Openings cut in the main building's walls allowed the fabricated struts, which consisted of inverted T-sections welded to wider top flange plates, to be installed from the courtyard. The top flange of each drag strut was bolted with adhesive anchors to the underside of the slab. Because of the cramped connection, $1\frac{1}{4}$ -in.-diameter A490 bolts were used.

Peter A. Timler, P.E., is a senior structural engineer, and John G. Sherstobitoff is a project manager with Sandwell Inc. in Vancouver. This article is based on a paper first presented at the 1994 National Steel Construction Conference.



•**S340 Metric Properties of Structural Shapes with Dimensions According to ASTM A6M:** This publication provides the metric dimensions and properties of all shapes listed in Part 1 of the *Manual of Steel Construction* according to ASTM A6M. (\$20.00)


AISC Bookstore



For more information on AISC publications, or to order any of the publications listed on this page, call **312/670-2400** or use AISC's handy fax information line by calling 800/644-2400.



•**S337 Simple Shear Connections (ASD):** This 119-page booklet contains numerous design aids, including double-angle web-bolted connections, structural tee single-shear connections, and single-angle connections welded to the support. (\$20.00)



•**H001 Highway Structures Design Handbook:** A two-volume guide for bridge consultants of the design of steel-framed superstructures, including: fatigue; fabrication; substructures; composite beam and plate girder bridges using both working stress and LFD methods; horizontally curved plate girder and box girder superstructures. (\$90.00)




•**S341 Seismic Provisions for Structural Steel Buildings:** This Specification covers seismic connection detailing and member design requirements for structural steel OMFs, SMFs, concentrically braced frames and eccentrically braced frames. (\$10.00)



Setting Standards For Over 70 Years

INDUSTRIAL REVOLUTION



An outdated, yet historic, steam plant proved the perfect new home for a pharmaceutical research company

BY TERRY LUNDEEN, P.E.,
TODD PERBIX, P.E., AND
JOHN SCHWARTZ, R.A.

FOR MORE THAN SEVEN DECADES, THE LAKE UNION STEAM PLANT provided auxiliary power for Seattle. But in 1984, the facility, located on the east shore of Seattle's Lake Union and visible from many vantages throughout the city, was decommissioned.

Sentiment and historic sensibilities demanded that the large concrete building be preserved. The original structure was built in three phases from 1911 to 1922—the end of the era when utilitarian buildings were designed as notable civic works. And the Lake Union Steam Plant was no exception—though essentially a 300-ft. by 90-ft. trapezoid, it featured exquisitely detailed monolithic concrete spandrels.

After the plant was closed, Seattle City Light tried unsuccessfully to find a new use or buyer for the property. Finally, in 1989, the Koll Company approached the City with a proposal to convert the building into a 109-unit condominium. Unfortunately, financing could not be obtained for the project. After other uses were evaluated, a plan was developed to convert the building into a research/office building with Zymo-Genetics, the American research arm of a large Danish pharmaceutical company, as tenant.

EXISTING STRUCTURE


The building was supported on 30-in. to 36-in. square concrete columns. These columns are spaced 16-ft. on center in

three longitudinal rows with spacings of 34-ft. and 51-ft. between rows. On the perimeter, the columns were interconnected with deep spandrels, providing lateral stiffness.

There were two primary operating levels in the original building: The basement and the main floor located 20 ft. above the basement. The basement and main floor were cast-in-place concrete beam and slab structures designed for heavy industrial loads up to 600 psf and were supported on the main columns along with a labyrinth of intermediate columns. Isolated from the main structure, the generators were located on the main floor. The main floor and columns below supported the boilers, which were constructed with a steel skeleton and brick shell. The boilers supported the 92-in.-diameter steel smoke stacks, which extended 105-ft. above the roof. In turn, the stacks were laterally supported by guy wires attached to the top of the concrete columns.


The roof was supported on steel trusses, which spanned between the three column rows. The top chords of the trusses were pitched, with the truss depth varying from 5-ft.-9-in. to 7-ft.-9-in., and the bottom chord was located 38 ft. above the main floor. The trusses were constructed of riveted double angles with chord cover plates. Most trusses were unique, due to the phased construction and the varying openings for stacks. The roof itself comprises a cast-in-place concrete slab supported on steel purlins, which framed into the panel points of the truss top chord. At the northwest corner of the building, a penthouse housed transformers and switchgear. The penthouse floors and roof were supported on deep concrete beams that span in the transverse direction.

Since the building was located over the edge of Lake Union, it was supported on approximately 2,000 12-in.-diameter piles. Controlled by locks downstream



Three stages of evolution: the original steam plant under construction (top left); after completion in the 1920s (middle left); and as it looks today (opposite).

Shown below is the roof framing plan of the current building.



near Puget Sound, the lake is set at two levels each year. The pile caps were set such that the tops of the piles would always be submerged. The mud line varies from 10 ft. below to 2 ft. below the bottom of the pile caps.

REDEVELOPMENT PLAN
Initial design studies conclud-

ed that a typical lab module, at the east and west sides of the building with a common service core in between, would fit well into the existing shell. This layout, coupled with the sites proximity to the University of Washington and the new campus for the Fred Hutchinson Cancer Research Center and its conve-

CALL TODAY FOR YOUR FREE DEMO KIT!

STRUCTURAL MATERIAL MANAGER 5.0

SMM 5.0 gives fabricators and detailers the fastest, most accurate material list manager available. No more time-consuming manual calculations!

The software's speed and efficiency delivers an easy-to-use system that's second to none. Call today for a FREE, no-obligation demo disk with all modules and the complete system's user's guide.

Let SMM 5.0 turn your next material list into hands-off experience!



- Main Module computes weights, surface areas, bolt counts & lineal totals
- Length-Nesting module produces optimal cut lists from in-house stock, vendor stock or the best combination of both
- Plate-Nesting Module draws the best layout for cutting plates from stock sheets
- Estimating Module tallies material costs, shop hours & field hours
- Production-Control Module prints shipping lists, loading tickets & job status reports

E.J.E. INDUSTRIES, INC.

287 Dewey Avenue, Washington, PA 15304

1-800-321-3955 or 412-228-8841

HANDS-OFF EXPERIENCE.

Please circle # 46



nient in-city location, made it ideal for its new tenant.


Since the building is a designated Landmark Structure, the Seattle Landmarks Preservation Board had to approve all changes, modifications or repairs to the structure. In addition, a great deal of input was provided by a Citizens Advisory Committee. Changes to the structure included replacement of the original stacks, replacement of the window system, integration of new floor lines, penthouse expansion to support new stacks, interior layouts, and the configuration and finish of added diagonal bracing.

The programming phase of the project started with detailed discussions with individual senior scientists to outline each lab's function, equipment needs, proximity requirements, mechanical and lab gas requirements and other special needs or desires. This process also was conducted for all support and administration departments. The process detailed a need for approximately 95,000 sq. ft. at the time of initial occupancy. ZymoGenetics also desired predominately clearspan lab spaces and a well organized mechanical distribution system that would easily accommodate future modifications or expansion. In addition, the company wanted labs

SHOP DETAILS with AutoCAD®

Version 5.3

If your present CAD system doesn't detail everything you fabricate, then you should look at one that does - in English or Metric.




COMPUTER DETAILING CORPORATION

A service company for Steel Fabricators and Detailers

80 Second Street Pike - Suite 10
Southampton, PA 18966


215-355-6003

Fax 215-355-6210



NEW

OCP An Optimal Cutting Program for linear nesting (multiling) to optimize cutting lists for maximum savings - current stock, warehouse, or both. Introductory price \$ 169.00



oriented to the exterior of the building to take advantage of the views and natural light, grouping offices in the center of the building to encourage informal interaction between the various scientists, and providing a design that expressed the dynamic and exciting work in which the company is involved.

By utilizing a negotiated construction contract and design-built subcontractors for the mechanical, electrical and plumbing contracts, these individuals were identified early and were available to assist the design team at the start, where there input could have the greatest benefit.

As the design team developed various options, it became apparent that the vertical floor clearance at the labs would be critical. With the height and bulk variances limiting any potential expansion of the building envelope, the substantial space required for lab mechanical systems, and a stringent client budget limit, a three-floor scheme was identified for the interior of the main Steam Plant building. This scheme also accommodated the clients desire to incorporate a limited interstitial access concept within the ceiling spaces at the second and third floor labs. An original concept to provide steel catwalks in this area was

eliminated for cost reasons, but the vertical clearance still allows access for future work on the building systems.

GRAVITY FRAMING SYSTEM

Before attempting to develop structural schemes, it was necessary to evaluate the existing building and understand its limitations.

The main columns were adequate with the exception of an insufficient cover of reinforcement and segregation of aggregate at cold joints. Cores from the boiler support columns indicated that the average compressive strength was 2,500 psi. The steel trusses were in excellent condition and chemical testing confirmed weldability. The major area of concern, then, was the piles. However, a foundation survey by divers confirmed the size and condition of the piles and core samples showed no deterioration of the wood.

Given concerns with known hazardous materials below the basement level, it was clear that foundation work needed to be minimized. Fortunately, the geotechnical engineer on the project discovered a 1915 University of Washington research paper on the construction of the building that provided information on pile lengths and blow counts. Based on this information, and the new


MAX WEISS

STEEL SHAPING SPECIALISTS



UNUSUAL SHAPES AREN'T UNUSUAL AT MAX WEISS.

ROLLING & FORMING
BLACKSMITHING
WELDING & MACHINING
INDUSTRIAL AND CONTRACTORS SUPPLIES



IRREGULAR CURVES,
VERTICAL OFFSETS,
ELLIPTICAL SHAPES,
CIRCLES, OR SEGMENTS
WITH OR WITHOUT TANGENTS

If it's structural steel that needs to be bent, for major architectural projects or for unique applications, chances are, Max Weiss bends it. If you have a question or problem in bending, call, FAX or write Dept. M93 for a solution. **TAKE IT TO THE MAX.**



MAX WEISS CO., INC.
8625 W. Bradley Road
Milwaukee, WI 53224 USA
Telephone: 414-355-8220
MAX FAX 414-355-4698



borings, the allowable pile capacities were set at 30 tons and the allowable existing and future loads on pile caps were calculated. The roof structure also was analyzed, as was the main floor

structure.

The lab space and parking requirements, along with the foundation considerations, were the driving factors in developing the framing layout. While the total load on the foundation would decrease significantly from the original use, many of the pile caps were located in areas that needed to be column free. An initial attempt to utilize only the three primary existing column lines was unsuccessful because the piles at the central columns would be overloaded. Thus, a fourth column line was established, which resulted in transverse column spacing of 35 ft., 15 ft. and 35 ft. Because of the location of existing pile caps, the longitudinal spacing of the new columns did not align with the 16-ft. skewed module of the existing columns. The framing and architectural floor layouts were adjusted to accommodate this misalignment.

In order to maximize the floor-to-floor space in the labs for mechanical systems, the parking levels were located as low as possible. The existing basement structure was used for the lower parking level and the upper parking level was constructed as a transversely post-tensioned concrete slab with mild reinforced wide shallow longitudinal beams to minimize structure depth.

The three main office and lab floors were framed with composite steel beams. A post-tensioned slab, similar to the parking level, also was considered. However, while somewhat thicker, the steel framing was found to be more cost effective for the higher lab floor loads. Additionally, the owner had concerns that a post-tensioned slab would limit future floor penetrations. Finally, complex connections would have been required to allow the slab to freely shorten and creep with-

Making the Difference When Performance, Reputation and Quality Count.

- FULL TRACEABILITY
- LOT CONTROL
- CERTIFICATIONS

Registered head markings on all structural and machine bolts.



All products made from steel melted and manufactured in the U.S.A.



St. Louis Screw & Bolt Company

6900 N. Broadway St. Louis, MO 63147 U.S.A.
1-800-237-7059/(314)389-7500/FAX (314)389-7510



Associate

out distressing the relatively stiff existing columns. The steel framing also had a scheduling advantage over all cast-in-place options since it allowed top-down construction.

The longer span beams are W18s and the purlins and shorter beams are W12s and W14s. All wide flange material was ASTM A572 Grade 50. The framing was arranged orthogonally wherever possible to minimize skewed connections. Floor edge beams were set back 42 in. from the window line to satisfy historical requirements for the building elevations. The deck edges were then stiffened with 7-in. channels to meet tight deflection tolerances for the custom window frames.

While the owner was concerned with floor vibrations, they felt that most of their sensitive equipment would have to be locally isolated regardless of structure type. Even so, vibration characteristics were somewhat improved compared with typical office construction by using a 4 1/2-in. normal weight topping slab over a 2-in. metal deck. In addition, the extra slab thickness attained a two-hour fire rating without fireproofing the deck.

The expanded penthouse contains several unique framing systems. The floor-to-floor heights established by the existing parapet height made it difficult to obtain functional lab space. In the penthouse addition, four column lines were established that limit span lengths. Three of these lines aligned with either existing or new columns below.

The fourth line is supported on transfer girders at the lower penthouse level. These transfer girders were made of built up W12/WT12 sections placed as close as possible to the existing roof, establishing the new floor level. With the shorter spans above, no transverse framing was necessary and longitudinal runs of mechanical and lab services could be installed directly

to the bottom of the floor slab.

CONNECTIONS

Single shear plates were used for the steel-to-steel connections wherever possible. Due to limited beam depths and high loads, some double angle connections also were specified. All connections were made with horizontal slots, since there is no chance to "plumb" columns in a large renovation project.

The steel-to-concrete connections were perhaps the most critical structural element. Since they had to be fire rated, epoxy anchors were not an option. Thru-bolting the columns also was not feasible because, in addition to the high cost, the bolts would have been visible on the historic exterior building finish. Instead, high capacity expansion anchors, with ICBO certified allowable shear loads exceeding 7,500 lbs., were specified. Typical connections contained eight of these 3/8-in. bolts spaced at approximately 8-in. on center. Because of the uncertainty of the concrete condition at each anchorage, a load-indicating type option was selected for the bolts.

SEISMIC DESIGN

As with any major renovation in Seattle, developing appropriate seismic criteria is an important project consideration. Due to the change-of-use and extensive demolition in this project, an extensive seismic retrofit was mandated. While the building had withstood two major earthquakes without any sign of damage and the total weight of the building was being reduced with the removal of heavy equipment, the new floors created new load paths in the non-ductile concrete frame. Although the structure had significant strength and stiffness, its ability to withstand a subduction zone type earthquake of long duration was questionable. Therefore, a new seismic system, designed to resist current UBC Zone 3 forces, was designed.



THE CADVANTAGE DETAILING SYSTEM WON'T DRIVE YOU INSANE.


CadVantage Structural performs all calculations, matches connections and figures member clearances automatically. The program prepares advance material lists (and applies M.O. #s), applies AISC weld symbols, writes bills of materials, creates title blocks, checks for logical input and more. It's easy - and your job productivity and profits will never get the ax.

CadVantage®

619 South Cedar Street • Studio A
Charlotte, North Carolina 28202

704-344-9644

Please circle # 45



In order for the new lateral system to be effective, it needed to be stiffer than the existing spandrel frames. The choices boiled down to steel concentric braced frames and/or concrete shear walls. As for the gravity framing, foundation considerations were paramount in locating the new lateral systems. Specifically, the overturning forces were limited by the compression pile capacity. Additionally, given the timber pile/concrete pile cap interface, no net tension forces could act on a pile cap. In the longitudinal

direction, the obvious location for the primary system was along the existing central column line. Because the lab spaces could not be interrupted in the transverse direction, overturning forces on internal elements with resulting high aspect ratios were excessive. After several options for transverse interior core elements with outriggers to exterior columns were considered, exterior bracing elements were selected.

The main bracing system consists of shear walls in the parking levels below the first floor

and steel braced frames above. To preserve the industrial character of the building, all of the 10-in. and 12-in.-diameter pipes are exposed and architecturally featured. The existing columns are part of the longitudinal braced frame. Since concrete columns are not allowed in Zone 3 braced frames in new construction, the columns were evaluated for strength under amplified ($\frac{3}{8} R_w$) earthquake loads. Because three of the 12 existing exterior columns are unreinforced brick infill, the transverse-braced frames were set just inside the building and include new steel columns. In addition to resisting primary frame forces, the columns also were used to strongback the historic brick infill. Torsional forces, resulting from the single offset longitudinal element, are resisted by the exterior transverse elements. Lateral loads in the penthouse are resisted in the transverse direction with steel braced frames and in the longitudinal direction with concrete shear walls.

There are several unique diaphragm elements in the structure. Because it was difficult to transfer tensile drag forces through the existing columns to the longitudinal braced frame, a collector element was developed at the adjacent new column line. The beam sizes along this line were increased for axial forces and the tensile connection forces were resisted with full penetration flange welds. Diaphragm chord forces at the large central slot in the building are resisted by 5-in. structural tubes. Tensile forces in these tubes are developed with pairs of 30-ft.-long, $1\frac{3}{8}$ -in. high-strength threaded rods, extending through two existing columns. Areas of the existing roof diaphragms that were not sufficient to transfer forces to the exterior frames are supplemented with topping slabs.

The connections between the new and existing elements in the lateral system were quite chal-

09-157

lenging. Recognizing their importance, the connections were designed for amplified forces according to the current code. Among a host of special conditions, the steel-to-concrete connections in the longitudinal braced frame received the most scrutiny. Steel channels were installed from floor-to-floor to distribute vertical frame forces to epoxy anchors. Each 1 1/4-in. anchor has an ultimate shear capacity of 62 kips and in-place load tests were performed beyond this level as part of a contractor substitution submittal. Given the concrete strength, spacing and edge distance requirements, this appears to be the maximum load per unit length that can be obtained with any product on the market. These channels and anchors also are exposed in the finished building.

Using ETABS software, a three-dimensional structural model was developed of the building, containing all new and existing elements that contributed to the lateral stiffness. The structure was analyzed to assure that no existing elements were overloaded. The next step in the analysis was to remove all existing elements and verify the adequacy of the new frames and shear walls. Dynamic analysis was performed since the structure had many of the vertical and plan irregularities listed in the UBC. The foundation was modelled with vertical, lateral, and plan rotational springs to properly evaluate the loads on the piles.

This article was condensed from a paper delivered at the 1994 National Steel Construction Conference. Terry Lundeen was an associate with the Seattle structural engineering firm Ratti Swenson Perbix, Inc. and is currently with Coughlin Porter Lundeen. Todd Perbix is a principal with Ratti Swenson Perbix, Inc. John Schwartz is the managing associate at the Seattle architectural firm Daly & Associates.

IN STOCK!

YOUR SOURCE FOR HIGH STRENGTH WEATHERING & ABRASION RESISTANT STEEL

HIGH STRENGTH WEATHERING

A588

BARS • SHAPES • PLATES
FLATS • ROUNDS • SQUARES
ANGLES • CHANNELS • BEAMS

A242-1

PLATES

A606-4

HOT ROLLED COILS & SHEETS

HIGH STRENGTH

A572-50

BARS • SHAPES
FLATS • ROUNDS • SQUARES
ANGLES • CHANNELS • BEAMS

ABRASION RESISTANT

AR 360

PLATES

Hardox 400 & 500

PLATES

QUENCHED & TEMPERED

A514 Gr. A

PLATES

A517 Gr. E

PLATES



Central Steel Service, Inc.

1-800-868-6798

P.O. Box 326 • Pelham, AL 35124

205/664-2950 • Fax 205/663-3391

Please circle # 65

ATTENTION TO DETAIL



Computer Detailing Systems, Inc. introduces a state of the art structural steel detailing system which allows fabricators and detailers to meet the demands of the future with the ability to generate connection calculations, download to CNC equipment and interface with major design firms through the Steel Detailing Neutral File.

A practical, flexible system requiring minimal training, CDS is capable of producing intelligent 3D models, floor plans and elevations as well as shop drawings of unsurpassed quality using your standards and paper.

CDS is currently used by fabricators and detailers throughout the US and in Canada.

CONTACT COMPUTER DETAILING SYSTEMS today FOR A FREE INFORMATION PACK.

CDS

Structural Steel Detailing System

Computer Detailing Systems, Inc. • 7280 Pepperdam Avenue • Charleston, South Carolina 29418 • (803)552-7055

Please circle # 63

Affordable Design Power

PC Compatibility.

SIMON Systems



For more than 20 years, many state DOTs and consultants have utilized U.S. Steel's SIMON mainframe program for the design of straight steel plate-girder bridges. Now, the American Institute of Steel Construction is offering this powerful program on a PC platform.

SIMON designs I-shaped and multiple single-cell box-shaped girders, with up to 12 continuous spans. SIMON produces complete designs in accordance with the latest AASHTO Standard Specification for Highway Bridges. This enhanced and updated version of SIMON has undergone extensive verification by several state DOTs and consultants.

SIMON is easy to use because the engineer follows the same logic and process as when designing a bridge manually. The entire system runs in MS-DOS and occupies less than 1 MB of hard-disk space.

Output from the SIMON program includes:

- Dead-load and maximum and minimum live-load moments and shears for variable-axle H or HS truck loading or for variable-wheel loading with up to 20 axles.
- An optimum design of the girder elements based on control parameters selected by the user.
- Performance ratios computed for each limit state at the critical cross sections of the girder along with a complete printout of all AASHTO specification checks.
- A complete bill of materials including locations, yield strengths, weights, lengths, widths and thicknesses of all webs, flanges and stiffeners.

Licensing of SIMON Systems for use on a personal computer is available for an annual subscription fee of \$300. During the subscription period, AISC will furnish program updates and enhancements along with telephone support on the use of the software at no additional charge. To order or for more information: Phone: 312-670-2400, Fax: 312-670-5403.



Setting Standards for over 70 Years

Please circle # 6

STRUCTURAL ENGINEERING SOFTWARE SURVEY

THE PROLIFERATION—AND IMPROVEMENT—OF STRUCTURAL ENGINEERING SOFTWARE makes choosing a package more and more difficult. Fortunately, many vendors are now offering demonstration disks.

Recently, to further help engineers choose a software package, *Modern Steel Construction* surveyed users of 22 software programs. The methodology of the survey involved asking each vendor for the names of 30 active users, with an emphasis on relatively recent purchasers of the program. Each of these users was mailed a survey and asked to return it in a postage paid reply envelope. The return rate averaged around 60%. To further control the survey, we asked how often a respondent uses the program and discarded responses from anyone using the program less than once a month.

The questions reported on the following pages are:

- How easy was it to become familiar with the program's features? (rate the program from 1 to 10 with 10 being easy to learn and 1 being very difficult)
- What was the quality of the provided documentation (rate the documentation from 1 to 10 with 10 being clear and complete and 1 being incomplete and difficult to understand)
- Does the vendor provide adequate customer service (rate customer service from 1 to 10 with 10 being excellent service and 1 being very poor service; if you haven't required customer service, please skip this question)

- How easy is it to use the program? (rate each of the following items from 1 to 10, with 10 being excellent and 1 being poor)

- ease of input
- quality of graphics
- ease of connection to printer/plotter
- output quality

- Does the program perform up to expectations? (rate the program's quality from 1 to 10, with 10 being it fulfills all of the vendors claims and 1 being it does not perform at all)

- Has the program increased your productivity? (rate the program for increased productivity from 1 to 10, with 10 being it has substantially increased your productivity and 1 being it has had no effect on productivity)

- Has the program provided good value for the price paid for it? (rate the program for cost vs. value, with 10 being an extremely cost effective program and 1 being a poor value)

- Would you recommend this program to others? (rate the program from 1 to 10, with 10 being definitely and 1 being no)

The answers to the above questions were computed for both **mode** (the most frequently occurring response) and **mean** (the average response).

Generally speaking, there appears to be a slight correlation between length of ownership and perceptions about a program, with the longer the length of ownership, the less positive the perception. One possible explanation for this is that longer users are more likely to be using

an older version of the program.

In addition to these questions, we asked about the operating system currently being used and which operating system is preferred. Most users are working on IBM-compatible computers (the only notable exception being users of the Macintosh-based Multiframe program). The vast majority are running DOS-based software, and surprisingly, about half prefer DOS to Windows. One possible explanation for a DOS preference is the existing comfort level that most engineers already have in that system. But just as likely is the realization that DOS-based programs will run quicker than Windows-based programs, especially on older computer systems.

We also asked about how easy it was to integrate the software with other applications. Most of the software packages performed very poorly in this area, though most vendors report that they are working on this area and expect substantially easier integration in the near future. We also asked whether program documentation includes information about program limitations and assumptions. For the most part, according to this survey, vendors are doing a good job of explaining this area.


Some vendors opted not to participate in this survey. Some information on some of these programs is included at the end of the survey results.

To receive more information on any program, simply circle the appropriate number on the reader service card near the back of this magazine. Finally, to receive information on all building programs, circle no. 100; for information on all bridge programs, circle 101.

Modal Response
Mean Response

AISC for AutoCAD


AISC
1 East Wacker Dr., Ste. 3100
Chicago, IL 60601
ph: 312/670-2400
fax: 312/670-5403
CIRCLE NO: 1



Draws end, elevation and plan views of W, S, M and HP shapes, American Standard Channels, miscellaneous channels, structural tees, single and double angles, and tubing and pipe.

CONXPRT


AISC
1 East Wacker Dr., Ste. 3100
Chicago, IL 60601
ph: 312/670-2400
fax: 312/670-5403
CIRCLE NO: 1



Designs double-angle, single-plate, end-plate, and single-angle connections, as well as directly welded and flange-plated connections and column stiffening.

DESCUS


Opti-Mate, Inc.
P.O. Box 9097, Dept. A
Bethlehem, PA 18018
phone: 610/867-4077
fax: 610/865-1030
CIRCLE NO: 53



Design and analysis of straight and curved steel girder bridges.

"Solve Your Next Problem in Minutes!"

CALL for
FREE Demo



Integrated
Engineering
Software


Visual Analysis™ for Windows® \$295
AnalysisGroup™ for DOS®/Windows \$295

8840 Chapman Road, Bozeman, MT 59715

1-800-707-0816

Please circle # 87

DAST™ Design and Analysis of Structures



The total software solution for complex structures.

2D/3D static, P-Delta, and dynamic analyses.

Steel and concrete design.

Interactive input generator.

Text editor with graphics.

Model verification.

Post-analysis features.

Stand-alone or integrated with AutoCAD®.

Displaced structures, bending moment/shear force diagrams, stress contours, and more.

DAS

Das Consulting, Inc.

Demo Package
Available
800-322-1487

865 Turnpike Street
North Andover, MA 01857
Tel 508-794-1487 Fax 508-685-1200

Please circle # 82

MODERN STEEL CONSTRUCTION Reader Service Card

Please type or print only

name _____
 company name _____
 address _____
 city _____ state _____ zip code _____
 () ()
 business telephone _____ fax number _____

For free information on advertisers and other companies mentioned in this issue, circle the appropriate number below:

1 2 3 4 5 6 7 8 9 10 11 12
 13 14 15 16 17 18 19 20 21 22 23 24
 25 26 27 28 29 30 31 32 33 34 35 36
 37 38 39 40 41 42 43 44 45 46 47 48
 49 50 51 52 53 54 55 56 57 58 59 60
 61 62 63 64 65 66 67 68 69 70 71 72
 73 74 75 76 77 78 79 80 81 82 83 84
 85 86 87 88 89 90 91 92 93 94 95 96
 97 98 99 100 101 102 103 104 105 106 107 108
 109 110 111 112 113 114 115 116 117 118 119 120
 121 122 123 124 125 126 127 128 129 130 131 132

Check this box to renew or start a **FREE*** subscription to *Modern Steel Construction* *This offer good only for practicing professionals within the U.S.

signature _____

1. Type of workPlease circle **all** that apply

- a. Bridges
- b. Office Buildings
- c. Hospitals
- d. Retail
- e. Industrial
- f. Schools
- g. Multifamily
- h. Institutional
- i. Low-Rise
- j. High-Rise

2. Your positionPlease circle **ONLY** one

- a. Owner/President
- b. Chief Engineer/Chief Architect/Department Head
- c. Staff Engineer/Staff Architect/Construction Manager
- d. Other

3. Type of businessPlease circle **ONLY** one

- a. Structural engineer
- b. Civil engineer
- c. Structural steel fabricator
- d. Other fabricator
- e. Educator/library
- f. Architect
- g. Building owner/developer
- h. Steel mill
- i. Erector
- j. Steel product manufacturer
- k. GC/CM
- l. Student
- m. Other

4. Reason for InquiryPlease circle **ONLY** one

- a. Information file
- b. Immediate or Future Purchase

Please type or print only

name _____
 company name _____
 address _____
 city _____ state _____ zip code _____
 () ()
 business telephone _____ fax number _____

For free information on advertisers and other companies mentioned in this issue, circle the appropriate number below:

1 2 3 4 5 6 7 8 9 10 11 12
 13 14 15 16 17 18 19 20 21 22 23 24
 25 26 27 28 29 30 31 32 33 34 35 36
 37 38 39 40 41 42 43 44 45 46 47 48
 49 50 51 52 53 54 55 56 57 58 59 60
 61 62 63 64 65 66 67 68 69 70 71 72
 73 74 75 76 77 78 79 80 81 82 83 84
 85 86 87 88 89 90 91 92 93 94 95 96
 97 98 99 100 101 102 103 104 105 106 107 108
 109 110 111 112 113 114 115 116 117 118 119 120
 121 122 123 124 125 126 127 128 129 130 131 132

Check this box to renew or start a **FREE*** subscription to *Modern Steel Construction* *This offer good only for practicing professionals within the U.S.

signature _____

1. Type of workPlease circle **all** that apply

- a. Bridges
- b. Office Buildings
- c. Hospitals
- d. Retail
- e. Industrial
- f. Schools
- g. Multifamily
- h. Institutional
- i. Low-Rise
- j. High-Rise

2. Your positionPlease circle **ONLY** one

- a. Owner/President
- b. Chief Engineer/Chief Architect/Department Head
- c. Staff Engineer/Staff Architect/Construction Manager
- d. Other

3. Type of businessPlease circle **ONLY** one

- a. Structural engineer
- b. Civil engineer
- c. Structural steel fabricator
- d. Other fabricator
- e. Educator/library
- f. Architect
- g. Building owner/developer
- h. Steel mill
- i. Erector
- j. Steel product manufacturer
- k. GC/CM
- l. Student
- m. Other

4. Reason for InquiryPlease circle **ONLY** one

- a. Information file
- b. Immediate or Future Purchase



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS MAIL PERMIT NO. 12522 CHICAGO, IL

POSTAGE WILL BE PAID BY ADDRESSEE

**MODERN STEEL
CONSTRUCTION**

c/o CREATIVE DATA SERVICES
650 S CLARK ST
CHICAGO, IL 60605-9960



Use these cards to request information from manufacturers and other companies mentioned in this issue. Simply circle the numbers referenced in the advertisement or article, fill out the rest of the information requested on the card, and either mail it to: Modern Steel Construction, Creative Data Center, 650 South Clark St., Chicago, IL 60605-9960 or fax it to: **312/922-3165.**



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES


BUSINESS REPLY MAIL

FIRST CLASS MAIL PERMIT NO. 12522 CHICAGO, IL

POSTAGE WILL BE PAID BY ADDRESSEE

**MODERN STEEL
CONSTRUCTION**


c/o CREATIVE DATA SERVICES
650 S CLARK ST
CHICAGO, IL 60605-9960



**MODERN STEEL
CONSTRUCTION**
Reader Service Card

SES Steel Design Package


Ecom Associates, Inc.
8324 N. Steven Road
Milwaukee, WI 53223
phone: 414/365-2100
414/365-2110
CIRCLE NO: 90



Includes both LRFD & ASD. Package offers steel beam, steel column, composite beam and quick steel design.

ETABS


Computer & Structures, Inc.
1995 University Ave.
Berkeley, CA 94704
phone: 510/845-2177
fax: 510/845-4096
CIRCLE NO: 31



Provides sophisticated 3D analysis of multi-story buildings using either ASD or LRFD. Includes AutoETABS, an analysis & drafting program running inside of AutoCAD.

FLOORVIB

Structural Engineers Inc.
537 Wisteria Dr.
Radford, VA 24141
phone: 703/231-6074
fax: 703/639-0713
CIRCLE NO: 78





Provides vibration tolerance evaluation of steel member-concrete slab floor using a variety of criteria, with a final report generated for each evaluation.

RISA-3D

Setting the Standard

Is *value* important to you when selecting structural software?

If so, you'll want to know that **RISA-3D** scored a **10** out of **10** rating for cost vs. benefit in the October '94 issue of *Structural Engineering Forum* magazine.



The best software isn't always the most expensive software!



RISA-3D is setting a new standard for quality vs. cost. Try our demo and see for yourself just how good structural design software can be!

Call or Fax us for a Free Demo

RISA
TECHNOLOGIES

26212 Dimension Dr. Suite 200
Lake Forest, CA 92630
Voice: 800-332-7472
FAX: 714-951-5848

Please circle # 40

 Modal Response
 Mean Response

GT Strudl
 Georgia Tech Research Corp.
 790 Atlantic Dr.
 Atlanta, GA 30332-0355
 phone: 404/894-2260
 fax: 404/894-8014
 CIRCLE NO: 71

Learning		8 6.4
Documentation		8 6.6
Customer Support		9 8.2
Input		8 7.4
Graphics		5 6.4
Connectivity		8 7.9
Output Quality		10 6.9
Performance		10 8.7
Productivity		8 7.8
Cost Vs. Value		9 7.2
Advice		8 8.3

Finite element analysis and structural design CAE system including member design & code checking, nonlinear static & linear dynamic analysis and a graphics modeler.

Images 3D
 Celestial Software
 2150 Shattuck Ave., Ste. 1200
 Berkeley, CA 94704
 phone: 510/843-0977
 fax: 510/848-9849
 CIRCLE NO: 91

Learning		10 8.6
Documentation		10 9.6
Customer Support		9 8.4
Input		9 7.5
Graphics		8 7.8
Connectivity		8 7.8
Output Quality		7 8.2
Performance		9 8.7
Productivity		8 8.5
Cost Vs. Value		9 9.1
Advice		10 8.8

2D-3D finite element analysis program offering shear & moment diagrams, P-Delta, static, modal & dynamic analysis, and AISC code check.

MDX
 MDX Software
 1412 Ridgemoor Court
 Columbia, MO 65203
 phone: 314/446-3221
 fax: 314/446-3278
 CIRCLE NO: 47

Learning		7 7.1
Documentation		10 7.1
Customer Support		10 8.7
Input		9 7.6
Graphics		6 7.3
Connectivity		8 8.1
Output Quality		9 8.4
Performance		9 8.4
Productivity		9 8.4
Cost Vs. Value		8 7.2
Advice		10 8.6

Design and analysis of curved and straight steel bridge girders, compliance with AASHTO specs, I girders, box girders and rolled shapes, ASD or LFD design, and metric units with conversions.

STRUCTURAL ANALYSIS SOFTWARE

developed by COMPU-TEC ENGINEERING

BEAMS AND FRAMES \$149.00

Interactively performs analyses of continuous beams and selected 2-D frames quickly and accurately. Convenient to use instead of larger, general purpose programs.

FRAME3D (Version 3.0) \$295.00

Performs structural analyses of space frame structures (2000 nodes maximum) for a variety of loading and support conditions. Element library includes beam, truss and spring elements. Model, deformed shape, shear and bending moment plot files are generated.

FRPLOT \$99.00

Transforms data files generated by **FRAME3D** into plots of 3-D structural models or deformed shapes. These plots may be viewed on a computer monitor or printed.

BMPLLOT \$99.00

Produces load, displacement, shear and bending moment plots for beam elements and load cases selected by the **FRAME3D** user. These plots may be viewed on a computer monitor or printed in color or black and white.

FRAME3D (Version 4.0) \$395.00

Includes all of the features of **FRAME3D** (Version 3.0) plus tension only elements for diagonal bracing, piping elements for piping analysis, curved beam elements and a library of AISC section properties.

SHORE \$195.00

Performs stress analyses of shells of revolution (pressure vessels, etc.) and axisymmetric solids using the finite element method.

FEM3D \$495.00

Performs finite element stress analyses of 2-D and 3-D structures for thermal and mechanical loading conditions. Element library includes plate bending elements, planar isoparametric elements and solid elements. Includes all of the features of **FRAME3D** (Version 4.0). Model, distorted shape and stress contour plot files are generated.

FEHEAT \$195.00

Calculates the temperature distribution in flat plates and 3-D solid structures using the finite element method.

PLOTIT \$149.00

Provides model, distortion and color contour plots for **FEM3D** and **FEHEAT** analysis programs. Plots may be viewed on a monitor or printed.

BASEPLATE \$149.00

Calculates bolt loads and the maximum stress in flexible, rectangular baseplates. Bolts (preloaded) and loads may be placed anywhere on the plate. Prying action is included using a nonlinear finite element approach.

FLATPLATE \$149.00

Calculates displacements and stresses in flat (rectangular or circular) plates with concentrated or distributed loads. Plates may rest on an elastic subgrade and edges may be free, simply supported, fixed or spring supported.

The user's manual for each program contains theoretical background, descriptions of input and output, and examples. Plotting programs support HP Laser Jet and Desk Jet printers.

For more information,
please contact:

COMPU-TEC ENGINEERING, INC.

16100 Chesterfield Parkway, Suite 246 • Chesterfield, MO 63017

(314) 532-4062 • FAX: (314) 536-2154

MERLIN-DASH
Opti-Mate, Inc.
P.O. Box 9097, Dept. A
Bethlehem, PA 18018
phone: 610/867-4077
fax: 610/865-1030
CIRCLE NO: 53

Learning	8	7.2
Documentation	8	7.1
Customer Support	9	8.5
Input	9	8.4
Graphics	7	6.7
Connectivity	9	8.2
Output Quality	8	8
Performance	8	8.2
Productivity	10	8.3
Cost Vs. Value	8	7.6
Advice	10	8.5

Bridge design using choice of WSD, LFD or LRFD DL+LL analysis in either English or metric units. Both tapered and parabolic members can be used.

Multiframe 3D
Graphic Magic
180 Seventh Ave., Ste. 201
Santa Cruz, CA 95062
phone: 408/464-1949
fax: 408/464-0731
CIRCLE NO: 92

Learning	10	9.4
Documentation	8	8.4
Customer Support	8	8.2
Input	9	9.1
Graphics	10	9.3
Connectivity	10	9.5
Output Quality	10	8.9
Performance	9	9.1
Productivity	8	8.8
Cost Vs. Value	10	8.9
Advice	10	9.3

Macintosh-based modelling program that includes special elements such as springs, prescribed displacements, member releases and pinned joints. Can use English or metric units.

Multiframe 4D
Graphic Magic
180 Seventh Ave., Ste. 201
Santa Cruz, CA 95062
phone: 408/464-1949
fax: 408/464-0731
CIRCLE NO: 92

Learning	10	8.8
Documentation	9	7.4
Customer Support	10	7.6
Input	10	9
Graphics	10	9.8
Connectivity	10	9.8
Output Quality	10	9
Performance	9	9.2
Productivity	9	9
Cost Vs. Value	10	9.3
Advice	10	9.7

Macintosh-based program provides completely graphical approach to structural modeling, analysis and interpretation of results. Includes database of U.S. and international shapes.

Finally. Larsa™ 4.0

The Power of Larsa, the Ease of Windows.™

At last, the most powerful structural and earthquake engineering software in the world is user-friendly. Now Larsa has a new Microsoft™ Windows based graphical user interface. With the new L-Tools of Larsa™, the software is easy to use whether you need to perform a nonlinear structural analysis on a dome, or a bridge analysis on a simple model. There are more than 14 new capabilities with 4.0, which make us even more expansive and flexible. Using Larsa 4.0, almost any structural engineer in your firm can access the power of the Larsa computational engine.

Also, the increased productivity from the improved access just might lower your manpower costs. Go figure.

CALL OR WRITE NOW TO ORDER OR TO ASK
ABOUT THIS REVOLUTIONARY NEW RELEASE.
800 LARSA-85 OR 212.736-1616
330 W 42 St. New York, NY 10036




LARSA

Please circle # 88


 Modal Response
 Mean Response

RAMSBEAM
 Ram Analysis
 5315 Avenida Encinas, Ste. 220
 Carlsbad, CA 92008
 phone: 619/431-3610
 fax: 619/431-5214
 CIRCLE NO: 81




Single steel/steel composite beam program for ASD or LRFD. Includes almost any loading condition, frame checking, interactive trial designs, partial or full composite, and a library of shapes.

RAMSTEEL
 Ram Analysis
 5315 Avenida Encinas, Ste. 220
 Carlsbad, CA 92008
 phone: 619/431-3610
 fax: 619/431-5214
 CIRCLE NO: 41



Analysis, design & drafting of gravity load resisting members of steel-framed buildings. ASD & LRFD. Includes interface to CONXPRT software for connection design.

RISA 2D
 RISA Technologies
 26212 Dimension Dr., #200
 Lake Forest, CA 92630
 phone: 800/332-7472
 fax: 714/951-5848
 CIRCLE NO: 40



Static analysis & design of frames, trusses, beams, shear walls and retaining walls.


RAMSTEEL Asks: "How Much Time Do You Spend On These Tasks?"

See how RAMSTEEL can help you do this work in a *fraction of the time!*

30-DAY TRIAL AVAILABLE



- ▲ Computing tributary loads, computing live load reductions and tracking the reaction of one member to the next.
- ▲ Designing beams, girders, bar joists, joist girders, columns and base plates.
- ▲ Preparing calculations and creating framing plans.



INTEGRATED ANALYSIS,
 DESIGN AND DRAFTING OF
 STEEL BUILDINGS

Ram Analysis
 5315 Avenida Encinas,
 Suite M, Carlsbad, CA 92008
 Tel 800-726-7789
 Fax 619-431-5214
Please circle # 41

AutoSD Steel Detailing

At last, the sensible detailing program written by detailers for detailers. Menu driven means easy to use. Supported by numerous graphics means easy to learn. See what you are drawing as you draw it. You stay in control.

Detail beams, columns, braces, gusset plates, stairs, stair rails.

Automated Steel Detailing works with AutoCAD® release 9.0 or later.

\$3950.00

Calculator Programs

Calculate gusset plates, end connections, tearout, camber axial connections, oblique & right triangles, circles, and a Ft-inch calculator that emulates an HP® and more. For DOS 3.0 and higher with EGA or better.


\$250.00

For more information write:

AutoSD, Inc.
4033 59 PL
Meridian, MS 39307
(601) 693-4729


Please circle # 59

RISA 3D
 RISA Technologies
 26212 Dimension Dr., #200
 Lake Forest, CA 92630
 phone: 800/332-7472
 fax: 714/951-5848
 CIRCLE NO: 40




Includes static and dynamic analysis, P-Delta effects and steel design. Includes shape library. Extensive graphics allow true scale rendering, as well as rotation & zooming.

ROBOT V6
 Metrosoft, Inc.
 332 Paterson Ave.
 East Rutherford, NJ 07073
 phone: 201/438-4915
 fax: 201/438-7058
 CIRCLE NO: 51



Fully integrated graphical system for structural analysis & design in LRFD & ASD. Linear & non-linear static and buckling, P-delta and dynamic analysis. Includes interface to CONXPRT.

SAP90
 Computer & Structures, Inc.
 1995 University Ave.
 Berkeley, CA 94704
 phone: 510/845-2177
 fax: 510/845-4096
 CIRCLE NO: 31



Large capacity structural analysis program for bridges & buildings. Finite element, static and dynamic analysis using ASD or LRFD. Included are graphical pre- and post-processors.

GT STRUDL.

on a PC—It's All There!

Quality Performance Customer Support

The premier structural software engineers have been using since 1978 on mainframes and workstations is now available on PCs.

GT STRUDL provides the top quality, versatile, and accurate structural engineering and design software for utility, transportation, offshore, industrial, and civil works facilities.

GT STRUDL features include:

- interactive graphics
- links to popular CAD systems
- library of over 100 element types
- steel and reinforced concrete design
- static, nonlinear, and dynamic analyses
- graphical frame and finite element modeling
- compliance with NRC and ISO 9000 quality requirements
- operates on PCs, UNIX workstations, and mainframe computers
- voted #1 in user support

30-day trial available



Please circle # 71


For more information, please contact:

(404) 894-2260 FAX: (404) 894-8014

Computer Aided Structural Engineering Center Atlanta, GA 30332-0355 USA


 Modal Response
 Mean Response

SDI Floor
 Steel Deck Institute
 P.O. Box 9506
 Canton, OH 44711
 phone: 216/493-7886
 fax: 216/493-7886
 CIRCLE NO: 77




Set of expert knowledge systems for design of composite and non-composite bays, beams and girders using LRFD. Used to determine most economic design solution.

SIMON Systems
 AISC
 1 East Wacker Dr., Ste. 3100
 Chicago, IL 60601
 ph: 312/670-2400
 fax: 312/670-5403
 CIRCLE NO: 1



PC software system for the design of straight steel plate girder bridges. Designs I-shaped or multiple single-cell box-shaped girders with up to 12 continuous spans (and may include hinges).

STAAD-III/ISDS
 Research Engineers, Inc.
 22700 Savi Ranch Parkway
 Yorba Linda, CA 92687-4613
 phone: 714/974-2500
 fax: 714/974-4771
 CIRCLE NO: 34



Analysis includes linear and non-linear 2D/3D static/dynamic/seismic/P-Delta, frame/plate/shell elements and all loading & support conditions. Uses both ASD and LRFD.

Curved & Straight Steel Bridge Design

English & Metric

Serious Design Power on Your PC

- Complex grid and roadway geometries, I girders, box girders, rolled shapes
- Influence surface (grid) or influence line approach (grid or line girder)
- Powerful nonprismatic girder optimization processing (curved and straight)
- 1992 AASHTO Spec. w/ 1993 interims & 1993 Curved Girder Guide Spec.

30-day trials available

Call for Free Demo Version



MDX software

Phone (314) 446-3221
 Fax (314) 446-3278

Please circle # 47

DESCON

DESIGNS AND DETAILS STEEL CONNECTIONS



FOR A FREE DEMO DISK
CALL OR WRITE TO

OMNITECH ASSOCIATES
 P.O. BOX 7581
 BERKELEY, CA 94707
 (510) 658-8328

Please circle # 52

SteelPlus
 Barry Bowen Associates
 3394 Coleman Road
 Memphis, TN 38128
 phone: 901/373-6468
 fax: 901/373-6468
CIRCLE NO: 48

Learning	9
Documentation	8.5
Customer Support	8.8
Input	8.9
Graphics	9.7
Connectivity	8.6
Output Quality	9
Performance	8.6
Productivity	9
Cost Vs. Value	9.2
Advice	9.6

Drafting/detailing of structural shapes. Includes all structural shapes (W shapes, channels, angles, tubing, M, S, HP shapes and tees) listed in 9th Edition Manual of Steel Construction.

OTHER STRUCTURAL ENGINEERING SOFTWARE

ANALYSISGROUP
 Integrated Engineering Software
 8840 Chapman Road
 Bozeman, MT 59715
 phone: 406/586-8988
 fax: 406/586-9151
CIRCLE NO: 87

Suite of six specialized analysis tools for the rapid analysis of rectangular plates, continuous beams, mat footings, beams on elastic foundations, circular tanks, and shear wall rigidity problems.

DAST
 Das Consulting, Inc.
 865 Turnpike St.
 North Andover, MA 01845
 phone: 508/794-1487
 fax: 508/685-7230
CIRCLE NO: 82

Integrated package offering 2D/3D static including P-Delta, seismic and dynamic analysis and steel

& concrete design per American, Canadian, and other International codes & standards.

OPIMIZER
 Engineering Design Automation
 1600 Riviera Ave., Ste. 300
 Walnut Creek, CA 94596
 phone: 510/933-2525
 fax: 510/933-1920
CIRCLE NO: 93

Stand-alone program for 3D frame analysis & steel design. Includes: properties & component library; advanced static & dynamic analysis; post processing; code checking; optimal member resizing; and CAD interfaces.

SC-BRIDGE
 SC Solutions, Inc.
 1451 Grant Road
 Mountain View, CA 94040
 phone: 415/903-5050
 fax: 415/691-9452
CIRCLE NO: 94

Generates both stick and 3D models for dead load, live load and seismic analysis to be used with either GT STRUDL or ADINA. Includes both open steel and concrete box girders.

SABRE
 Opti-Mate, Inc.
 P.O. Box 9097, Dept. A
 Bethlehem, PA 18018
 phone: 610/867-4077
 fax: 610/865-1030
CIRCLE NO: 53

Reduces time needed to analyze/design highway sign structures and creates more efficient structures. Models and prismatic or tapered steel members for most-used tower and beam configurations.

STRU CAD*3D
 Zentech, Inc.
 8582 Katy Freeway, #205
 Houston, TX 77024
 phone: 713/984-9171
 fax: 713/984-9175
CIRCLE NO: 95

Graphics-oriented FEM design package including: elastic supports; permanent settlements; torsion design checks; 3- and 4-node plate elements; truss elements; code checks, static, dynamic & seismic analysis; machine vibration analysis; material takeoffs; and section libraries.

SODA—STRENGTHENING OPTIMIZATION DESIGN & ANALYSIS

Acronym Software
 22 King St. St., #302
 Waterloo, Ontario N2J1N8
 Canada
CIRCLE NO: 96

Automatically designs least-weight 2D or 3D steel frame or truss from a library of commercially available steel sections. Includes: ASD, LRFD and CISC; and P-Delta and first order design & analysis.

TRAP-Jr.
 Opti-Mate, Inc.
 P.O. Box 9097, Dept. A
 Bethlehem, PA 18018
 phone: 610/867-4077
 fax: 610/865-1030
CIRCLE NO: 53

Performs an analysis or group loading of a simple or continuous truss having up to six spans. Output includes verification of truss geometry, a force summary for DL+LL+I, and inventory, operating and post-ing ratings. New version includes LRFD & LFD.

VISUALANALYSIS
 Integrated Engineering Software
 8840 Chapman Road
 Bozeman, MT 59715
 phone: 406/586-8988
 fax: 406/586-9151
CIRCLE NO: 87

Windows-based general purpose finite element analysis package. Includes service & factored loads, smart combinations, response spectrums, static and dynamic analysis. Offers graphical results and context sensitive help.

WINSTRUDL
 C.A.S.T.
 P.O. Box 14676
 Fremont, CA 94539-4676
 phone: 510/226-8857
 fax: 510/226-7328
CIRCLE NO: 97

Windows-based general purpose finite element analysis program including static, P-Delta and dynamic analysis and AISC (ASD & LRFD) code checks.

Business Wanted

Individual wishes to purchase a structural steel fabricator with sales of 3 to 7mm/yr over last five years. I will consider any location in continental U.S. if business has been profitable and future prospects good. Reply in strict confidence to:

Business Wanted
2055 Vanderbilt Place
Atlanta, GA 30244

Working Construction Foreman

Wanted for a national merit shop single-story steel erector based in Indiana. Starting salary \$35,000 to \$40,000. No steel erection experience necessary—we will train. Travel 35 states. Fax resume to 317-984-3691.

StruCAD*3D

The Flagship Product for 3D Structural Analysis & Design

- Pop-Up & Pull-Down Menus
- Full 3D Graphics-Oriented
- Pre- and Postprocessing
- 3D AutoCAD Interface
- AISC-ASD, AISC-LRFD, ACI-318
- Reinforced Concrete Design
- Finite Element Analysis
- Wind & Gravity Load Generation
- Material Takeoff
- P-Delta and Thermal Analysis
- Pile-Soil Interaction
- Seismic & Machine Vibration
- Detailed Fatigue Analysis
- Prices Begin at \$249

Zentech, Inc.

8582 Katy Freeway, #205, Houston, TX 77024
Tel (713) 984-9171 Fax (713) 984-9175

GT STRUDL

ADINA

Static, Dynamic, Linear, Nonlinear & Pushover Analysis
Straight & Curved Steel Bridge Model & Load Generator

SC Solutions, Inc.

Tel (415) 903-5050 Fax (415) 691-9452

SC-Bridge

SC-Push3D

HEWLETT-PACKARD Computers/Peripherals

A complete line of used and refurbished HP Equipment to fill all your computer needs. Laser printers, scanners, disk drives, plotters (Draftpro, Draftmaster & Designjet), PC's and 9000 series workstations are available for immediate delivery. Call our toll free number for additional information and pricing.

Ted Dasher & Associates

4117 2nd Avenue South
Birmingham, AL 35222

800-638-4833 fax (205) 591-1108

Structural & Miscellaneous Steel Detailing CAD Programs

AutoCAD parametric LISP programs for preparing structural AND misc. steel shop drawings. All programs have been updated for 1995 and new programs have been added. Anchor bolts to roof opening frames and "everything between". Imperial and metric versions with USA, Canadian and European steel sections. 45-DAY MONEY BACK GUARANTEE. Discounts up to 30%. Buy only what you need. Used in the field for 8 years. Programs written by a detailer with 39 years experience. Extremely "flexible" programs. FREE telephone support. No maintenance fee. Reasonable yearly update fee. EXCELLENT PROGRAMS at a REASONABLE PRICE. Call for a FREE demo disk, list of programs, and prices.

SSDCP

110 Shady Oak Circle, Florence, MS 39073
Tel: 601/845-2146 (fax same)

Rolling

Beam-Angle-Tube-Pipe-Channel-Plate
Easy/Hardway Heavy Capacities

Up to **36"** W.F. Beam

209-466-9707

N.J. McCutchen, Inc.

123 W. Sonora St., Stockton, CA 95203

Images—3D

2D-3D Structural/Finite Element Analysis

- | | |
|--------------------------------|------------------------|
| Easy to learn and use | Automesh Generation |
| Shear & Moment Diagrams | Static, Modal, Dynamic |
| AISC Code Check | Enforced Displacements |
| Large Problems to 3,000 Joints | P-δ Analysis |

Complete Static Package—Only \$795

Celestial Software, 2150 Shattuck Ave., Suite 1200
Berkeley, CA 94704

Tel: 510-843-0977 / Fax: 510-848-9849

Fifty-node fully functional evaluation package for only \$49.95

NORTHRIDGE JAN. 17, 1994

EARTHQUAKE SLIDES/VIDEO

The one and only available technical slides showing close-up views of damages to Office Buildings, Hotels, Parking Structures, Bridges & Apartments. Each slide is explained individually.

Great material for discussions.

70 Photo Slides - \$89.00 Slides in a video cassette - \$49.00

Please send request & check/money order to: MA & Associates,
5105 E. Los Angeles Ave., Suite E157, Simi Valley, CA 93063




Phone/Fax (805) 579-8291

Advertisers' Index

Advertiser	Page Number	Circle No.
AISC Bookstore.....	35	
American Iron & Steel Institute	8	51
AutoSD.....	50	59
Nicholas J. Bouras.....	CII	33
C.D.S. Inc.....	43	63
Cadvantage.....	41	45
Central Steel.....	43	65
Chaparral Steel Co.....	11	43
Compu-Tec.....	48	85
Computer Detailing.....	38	
Computers & Structures Inc. (CSI).....	CIV	31
Cooperheat.....	33	56
Das Consulting.....	46	82
Design Data.....	7	32
EJE Industries.....	38	46
GTStrudl.....	51	71
Grinder Software.....	26	57
Integrated Engineering Software.....	46	87
LRFD Manual of Steel Construction.....	23	2
Larsa.....	49	88
MDX Software.....	52	47
Metrosoft.....	CIII	51
Mound Architectural Products.....	32	49
Nucor Yamato.....	28-29	39
Omnitech.....	52	52
Optimate.....	26	53
PC Simon.....	44	6
Ram Analysis.....	50	41
Research Engineers.....	5	34
RISA Technologies.....	32&47	40
St. Louis Screw & Bolt.....	40	36
Steel Deck Institute.....	34	77
Structural Engineers.....	27	78
TradeARBED.....	3	35
UNR Leavitt.....	14	79
Max Weiss Co.....	39	56
Whitefab.....	27	55

ROBOT V6

THE FINEST IN STRUCTURAL ANALYSIS AND DESIGN SOFTWARE



HIGHEST RATING

4.5

IN 1994
STRUCTURAL
ENGINEERING
SOFTWARE
SURVEY

Modern Steel
Construction
January '94

TOP RATING

10

FOR
COMPUTING
POWER

Structural
Engineering
Forum
March '94

NEW
RELEASE

NEW. Faster calculations.
NEW. Concrete design and detailing.
NEW. Interface to AISC's CONXPR1.
NEW. Completely revised, improved manual.

- very easy to learn and use, become a productive user in just one day
- extremely fast, shortens the concept through design cycle
- most powerful on PC platform - 3D FEM, buckling, nonlinear, P-delta, dynamic, 3D moving loads, parametric structures, phase constructions, US and foreign codes
- buy the power you need, starts from \$495 version - 150 node/3D plus plate elements
- no risk, 30 day money back guarantee

See for yourself. Have fun. Any questions? Call us. 1-800-60-ROBOT

Please circle # 51

332 Paterson Ave, E. Rutherford, NJ 07073

LIMITED WORKING VERSION OF PROGRAM WITH PRE-RECORDED EXAMPLES AVAILABLE. OVER 2000 USERS WORLDWIDE. FOR MORE INFORMATION CALL 201-438-4915 OR FAX TO 201-438-7058



metrosoft
STRUCTURES, INC.

ROBOT V6

Name: _____

Company: _____

Address: _____ State _____ Zip _____


Tel.: _____ Fax: _____

I am: structural engineer, architect, educator, dealer, other: _____

Please have a product specialist call me Please send more information

Please send working demo version (limited to 25 elements and 25 nodes), with recorded macros of real design examples. Enclosed is a check for \$25 (plus applicable Tax in NJ and NY). I have a system equal to or better than 386SX with math coprocessor, 4 MB 8 MB RAM, 25 MB of free disk space, VGA monitor.

Metrosoft Structures, Inc. 332 Paterson Avenue, E. Rutherford, NJ 07073. Tel 201 438-4915, Fax 201 438-7058.



MSC

STATE OF THE ART
Structural Engineering Software

INTEGRATED ANALYSIS AND DESIGN SOFTWARE FOR STRUCTURAL AND EARTHQUAKE ENGINEERING

Developed by Ashraf Habibullah & Edward L. Wilson



For further information:

Computers & Structures, Inc.
1995 University Avenue
Berkeley, California 94704

TEL: 510/845-2177
FAX: 510/845-4096

ETABS®
Building Analysis & Design

SAP90®
General Analysis & Design

Please circle # 31

ETABS is a registered trademark of Computers & Structures, Inc.
SAP90 is a registered trademark of Computers & Structures, Inc.